



Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

Wire Wheel Acid

Version number: GHS 2.0
Replaces version of: 2019-06-17 (GHS 1)

Revision: 2019-06-17

SECTION 1: Identification

1.1 Product identifier

Trade name

Wire Wheel Acid

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses

Acid based cleaner

Uses advised against

Do not use for squirting or spraying. Do not use for products which come into direct contact with the skin.

1.3 Details of the supplier of the safety data sheet

B&B Blending, LLC
10963 Leroy Drive
Northglenn CO 80233
United States

Telephone: 1.800.875.6320, 1.303.289.6320
e-mail: info@bbblending.com
Website: bbblending.com

e-mail (competent person)

btirrell@bbblending.com

1.4 Emergency telephone number

Emergency information service

USA 1.800.535.5053, INTL 1.352.323.3500
24 hr emergency information

SECTION 2: Hazard(s) identification

2.1 Classification of the substance or mixture

Classification acc. to OSHA "Hazard Communication Standard" (29 CFR 1910.1200)

Section	Hazard class	Category	Hazard class and category	Hazard statement
A.1O	acute toxicity (oral)	4	Acute Tox. 4	H302
A.1D	acute toxicity (dermal)	2	Acute Tox. 2	H310
A.1I	acute toxicity (inhal.)	2	Acute Tox. 2	H330
A.2	skin corrosion/irritation	1A	Skin Corr. 1A	H314
A.3	serious eye damage/eye irritation	1	Eye Dam. 1	H318
A.6	carcinogenicity	1A	Carc. 1A	H350
B.16	substance or mixture corrosive to metals	1	Met. Corr. 1	H290

For full text of abbreviations: see SECTION 16.

The most important adverse physicochemical, human health and environmental effects

Skin corrosion produces an irreversible damage to the skin; namely, visible necrosis through the epidermis and into the dermis.

2.2 Label elements

Labelling acc. to OSHA "Hazard Communication Standard" (29 CFR 1910.1200)

- Signal word danger

Wire Wheel Acid

Version number: GHS 2.0
Replaces version of: 2019-06-17 (GHS 1)

Revision: 2019-06-17

SECTION 3: Composition/information on ingredients

3.1 Substances

Not relevant (mixture)

3.2 Mixtures

Description of the mixture

Hazardous ingredients acc. to GHS				
Name of substance	Identifier	Wt%	Classification acc. to GHS	Notes
phosphoric acid	CAS No 7664-38-2	20 - < 40	Acute Tox. 4 / H302 Acute Tox. 2 / H330 Skin Corr. 1B / H314 Eye Dam. 1 / H318 Met. Corr. 1 / H290	IOELV
sulfuric acid ... %	CAS No 7664-93-9	3 - < 12	Acute Tox. 3 / H331 Skin Corr. 1A / H314 Eye Dam. 1 / H318 Carc. 1A / H350	B(a) IARC: 1 IOELV RoC "Known"
hydrofluoric acid ... %	CAS No 7664-39-3	3 - < 12	Acute Tox. 2 / H300 Acute Tox. 1 / H310 Acute Tox. 2 / H330 Skin Corr. 1A / H314 Eye Dam. 1 / H318	B(a) IOELV
Alcohols, C9-11 ethoxylated	CAS No 68439-46-3	1 - < 3	Acute Tox. 4 / H302 Acute Tox. 4 / H312 Eye Dam. 1 / H318	

Notes

B(a): The classification refers to an aqueous solution
IARC: 1: IARC group 1: carcinogenic to humans (International Agency for Research on Cancer)
IOELV: Substance with a community indicative occupational exposure limit value
RoC NTP-RoC: Known To Be A Human Carcinogen
"Known":

For full text of abbreviations: see SECTION 16. Exact percentage of ingredients is withheld as a trade secret.

SECTION 4: First-aid measures

4.1 Description of first-aid measures

General notes

Do not leave affected person unattended. Remove victim out of the danger area. Keep affected person warm, still and covered. Take off immediately all contaminated clothing. In all cases of doubt, or when symptoms persist, seek medical advice. In case of unconsciousness place person in the recovery position. Never give anything by mouth.

Following inhalation

If breathing is irregular or stopped, immediately seek medical assistance and start first aid actions. In case of respiratory tract irritation, consult a physician. Provide fresh air.

Following skin contact

Follow water rinsing by massaging with calcium gluconate (2.5%) gel. Continue massaging with gel while seeking medical attention.

Following eye contact

Remove contact lenses, if present and easy to do. Continue rinsing. Irrigate with calcium gluconate (1.0%) solution. Seek immediate medical attention.

Wire Wheel Acid

Version number: GHS 2.0
Replaces version of: 2019-06-17 (GHS 1)

Revision: 2019-06-17

Following ingestion

Rinse mouth with water (only if the person is conscious). Do NOT induce vomiting. If patient is conscious and able to swallow give oral calcium solutions or calcium based antacids or milk. Seek immediate medical attention.

4.2 Most important symptoms and effects, both acute and delayed

Delayed or immediate effects can be expected after short or long-term exposure. Risk of hypocalcemia (possible life threatening lowering of serum calcium). May cause severe chemical burns which may not be immediately apparent.

4.3 Indication of any immediate medical attention and special treatment needed

Immediately seek medical attention in any cases of exposure.

SECTION 5: Fire-fighting measures

5.1 Extinguishing media

Suitable extinguishing media

Water spray, Alcohol resistant foam, BC-powder, Carbon dioxide (CO₂)

Unsuitable extinguishing media

Water jet

5.2 Special hazards arising from the substance or mixture

Substance or mixture corrosive to metals.

Hazardous combustion products

Nitrogen oxides (NO_x), Phosphorus oxides (P_xO_y)

5.3 Advice for firefighters

In case of fire and/or explosion do not breathe fumes. Co-ordinate firefighting measures to the fire surroundings. Do not allow firefighting water to enter drains or water courses. Collect contaminated firefighting water separately. Fight fire with normal precautions from a reasonable distance.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

Remove persons to safety.

For emergency responders

Wear breathing apparatus if exposed to vapors/dust/aerosols/gases.

6.2 Environmental precautions

Keep away from drains, surface and ground water. Retain contaminated washing water and dispose of it. If substance has entered a water course or sewer, inform the responsible authority.

6.3 Methods and material for containment and cleaning up

Advices on how to contain a spill

Covering of drains

Advices on how to clean up a spill

Wipe up with absorbent material (e.g. cloth, fleece). Collect spillage: sawdust, kieselgur (diatomite), sand, universal binder

Appropriate containment techniques

Use of adsorbent materials.

Other information relating to spills and releases

Place in appropriate containers for disposal. Ventilate affected area.



Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

Wire Wheel Acid

Version number: GHS 2.0
Replaces version of: 2019-06-17 (GHS 1)

Revision: 2019-06-17

6.4 Reference to other sections

Hazardous combustion products: see section 5. Personal protective equipment: see section 8. Incompatible materials: see section 10. Disposal considerations: see section 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Recommendations

- Measures to prevent fire as well as aerosol and dust generation
Use local and general ventilation. Use only in well-ventilated areas.

Advice on general occupational hygiene

Wash hands after use. Do not eat, drink and smoke in work areas. Remove contaminated clothing and protective equipment before entering eating areas. Never keep food or drink in the vicinity of chemicals. Never place chemicals in containers that are normally used for food or drink. Keep away from food, drink and animal feedingstuffs.

7.2 Conditions for safe storage, including any incompatibilities

Managing of associated risks

- Corrosive conditions
Store in corrosive resistant container with a resistant inner liner.

Control of the effects

Protect against external exposure, such as

Frost

- Ventilation requirements
Keep any substance that emits harmful vapors or gases in a place that allows these to be permanently extracted.
- Packaging compatibilities
Only packagings which are approved (e.g. acc. to the Dangerous Goods Regulations) may be used.

7.3 Specific end use(s)

See section 16 for a general overview.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limit values (Workplace Exposure Limits)											
Country	Name of agent	CAS No	Identifier	TWA [ppm]	TWA [mg/m ³]	STEL [ppm]	STEL [mg/m ³]	Ceiling-C [ppm]	Ceiling-C [mg/m ³]	Notation	Source
US	phosphoric acid	7664-38-2	PEL (CA)		1		3				Cal/ OSHA PEL
US	phosphoric acid	7664-38-2	REL		1 (10 h)		3				NIOSH REL
US	phosphoric acid	7664-38-2	PEL		1						29 CFR 1910.1000

Wire Wheel Acid

Version number: GHS 2.0
Replaces version of: 2019-06-17 (GHS 1)

Revision: 2019-06-17

Occupational exposure limit values (Workplace Exposure Limits)											
Country	Name of agent	CAS No	Identifier	TWA [ppm]	TWA [mg/m ³]	STEL [ppm]	STEL [mg/m ³]	Ceiling-C [ppm]	Ceiling-C [mg/m ³]	Notation	Source
US	hydrogen fluoride	7664-39-3	REL	3 (10 h)	2.5 (10 h)			6 (15 min)	5 (15 min)		NIOSH REL
US	hydrogen fluoride	7664-39-3	PEL	3						F	29 CFR 1910.1000
US	hydrogen fluoride (hydrofluoric acid)	7664-39-3	PEL (CA)	0.4	0.33	1	0.83			F	Cal/OSHA PEL
US	sulfuric acid	7664-93-9	PEL (CA)		0.1		3				Cal/OSHA PEL
US	sulfuric acid	7664-93-9	REL		1 (10 h)						NIOSH REL
US	sulfuric acid	7664-93-9	PEL		1						29 CFR 1910.1000

Notation

Ceiling-C

ceiling value is a limit value above which exposure should not occur

F

calculated as F (fluorine)

STEL

short-term exposure limit: a limit value above which exposure should not occur and which is related to a 15-minute period (unless otherwise specified)

TWA

time-weighted average (long-term exposure limit): measured or calculated in relation to a reference period of 8 hours time-weighted average (unless otherwise specified)

Relevant DNELs of components of the mixture						
Name of substance	CAS No	Endpoint	Threshold level	Protection goal, route of exposure	Used in	Exposure time
phosphoric acid	7664-38-2	DNEL	2 mg/m ³	human, inhalatory	worker (industry)	acute - local effects
phosphoric acid	7664-38-2	DNEL	1 mg/m ³	human, inhalatory	worker (industry)	chronic - local effects
sulfuric acid ... %	7664-93-9	DNEL	0.05 mg/m ³	human, inhalatory	worker (industry)	chronic - local effects
sulfuric acid ... %	7664-93-9	DNEL	0.1 mg/m ³	human, inhalatory	worker (industry)	acute - local effects
hydrofluoric acid ... %	7664-39-3	DNEL	1.5 mg/m ³	human, inhalatory	worker (industry)	chronic - systemic effects
hydrofluoric acid ... %	7664-39-3	DNEL	2.5 mg/m ³	human, inhalatory	worker (industry)	acute - systemic effects
hydrofluoric acid ... %	7664-39-3	DNEL	1.5 µg/m ³	human, inhalatory	worker (industry)	chronic - local effects
hydrofluoric acid ... %	7664-39-3	DNEL	2.5 mg/m ³	human, inhalatory	worker (industry)	acute - local effects



Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

Wire Wheel Acid

Version number: GHS 2.0
Replaces version of: 2019-06-17 (GHS 1)

Revision: 2019-06-17

Relevant DNELs of components of the mixture						
Name of substance	CAS No	End-point	Threshold level	Protection goal, route of exposure	Used in	Exposure time
Alcohols, C9-11 ethoxylated	68439-46-3	DNEL	2,080 mg/kg	human, dermal	worker (industry)	chronic - systemic effects
Alcohols, C9-11 ethoxylated	68439-46-3	DNEL	294 mg/m ³	human, inhalatory	worker (industry)	chronic - systemic effects

Relevant PNECs of components of the mixture						
Name of substance	CAS No	End-point	Threshold level	Organism	Environmental compartment	Exposure time
sulfuric acid ... %	7664-93-9	PNEC	0.003 mg/l	aquatic organisms	freshwater	short-term (single instance)
sulfuric acid ... %	7664-93-9	PNEC	0 mg/l	aquatic organisms	marine water	short-term (single instance)
sulfuric acid ... %	7664-93-9	PNEC	8.8 mg/l	aquatic organisms	sewage treatment plant (STP)	short-term (single instance)
sulfuric acid ... %	7664-93-9	PNEC	0.002 mg/kg	aquatic organisms	freshwater sediment	short-term (single instance)
sulfuric acid ... %	7664-93-9	PNEC	0.002 mg/kg	aquatic organisms	marine sediment	short-term (single instance)
hydrofluoric acid ... %	7664-39-3	PNEC	51 mg/l	microorganisms	sewage treatment plant (STP)	short-term (single instance)
hydrofluoric acid ... %	7664-39-3	PNEC	0.9 mg/l	aquatic organisms	freshwater	short-term (single instance)
hydrofluoric acid ... %	7664-39-3	PNEC	0.9 mg/l	aquatic organisms	marine water	short-term (single instance)
hydrofluoric acid ... %	7664-39-3	PNEC	51 mg/l	aquatic organisms	sewage treatment plant (STP)	short-term (single instance)
hydrofluoric acid ... %	7664-39-3	PNEC	11 mg/kg	terrestrial organisms	soil	short-term (single instance)
Alcohols, C9-11 ethoxylated	68439-46-3	PNEC	0.1038 mg/l	aquatic organisms	freshwater	short-term (single instance)
Alcohols, C9-11 ethoxylated	68439-46-3	PNEC	0.1038 mg/l	aquatic organisms	marine water	short-term (single instance)
Alcohols, C9-11 ethoxylated	68439-46-3	PNEC	1.4 mg/l	microorganisms	sewage treatment plant (STP)	short-term (single instance)
Alcohols, C9-11 ethoxylated	68439-46-3	PNEC	13.7 mg/kg	benthic organisms	sediment	short-term (single instance)
Alcohols, C9-11 ethoxylated	68439-46-3	PNEC	13.7 mg/kg	pelagic organisms	sediment	short-term (single instance)
Alcohols, C9-11 ethoxylated	68439-46-3	PNEC	1 mg/kg	terrestrial organisms	soil	short-term (single instance)
Alcohols, C9-11 ethoxylated	68439-46-3	PNEC	0.014 mg/l	aquatic organisms	water	intermittent release



Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

Wire Wheel Acid

Version number: GHS 2.0
Replaces version of: 2019-06-17 (GHS 1)

Revision: 2019-06-17

8.2 Exposure controls

Appropriate engineering controls

General ventilation.

Individual protection measures (personal protective equipment)

Eye/face protection

Wear eye/face protection.

Skin protection

- Hand protection

Wear suitable gloves. Chemical protection gloves are suitable, which are tested according to EN 374. Check leak-tightness/impermeability prior to use. In the case of wanting to use the gloves again, clean them before taking off and air them well. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

- Other protection measures

Take recovery periods for skin regeneration. Preventive skin protection (barrier creams/ointments) is recommended. Wash hands thoroughly after handling.

Respiratory protection

In case of inadequate ventilation wear respiratory protection.

Environmental exposure controls

Use appropriate container to avoid environmental contamination. Keep away from drains, surface and ground water.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance

Physical state	liquid
Color	colorless to pale amber
Odor	sharp

Other safety parameters

pH (value)	not determined
Melting point/freezing point	not determined
Initial boiling point and boiling range	19.44 °C
Flash point	not determined
Evaporation rate	not determined
Flammability (solid, gas)	not relevant, (fluid)
Explosive limits	not determined
Vapor pressure	783 mmHg

Wire Wheel Acid

Version number: GHS 2.0
Replaces version of: 2019-06-17 (GHS 1)

Revision: 2019-06-17

Density	1.2 g/ml
Vapor density	this information is not available
Solubility(ies)	
- Water solubility	miscible in any proportion
Partition coefficient	
- n-octanol/water (log KOW)	this information is not available
Auto-ignition temperature	311 °C
Viscosity	not determined
Explosive properties	none
Oxidizing properties	none

9.2 Other information

Temperature class (USA, acc. to NEC 500)	T2 (maximum permissible surface temperature on the equipment: 300 °C)
--	---

SECTION 10: Stability and reactivity

10.1 Reactivity

Concerning incompatibility: see below "Conditions to avoid" and "Incompatible materials". Substance or mixture corrosive to metals.

10.2 Chemical stability

See below "Conditions to avoid".

10.3 Possibility of hazardous reactions

No known hazardous reactions.

10.4 Conditions to avoid

There are no specific conditions known which have to be avoided.

10.5 Incompatible materials

Oxidizers

10.6 Hazardous decomposition products

Reasonably anticipated hazardous decomposition products produced as a result of use, storage, spill and heating are not known. Hazardous combustion products: see section 5.



Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

Wire Wheel Acid

Version number: GHS 2.0
Replaces version of: 2019-06-17 (GHS 1)

Revision: 2019-06-17

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Test data are not available for the complete mixture.

Classification procedure

The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

Classification acc. to OSHA "Hazard Communication Standard" (29 CFR 1910.1200)

Acute toxicity

Harmful if swallowed. Fatal in contact with skin. Fatal if inhaled.

- Acute toxicity estimate (ATE)

Oral	1,047 mg/kg
Dermal	135.6 mg/kg
Inhalation: vapor	1.362 mg/l/4h
Inhalation: dust/mist	0.6303 mg/l/4h

Acute toxicity estimate (ATE) of components of the mixture

Name of substance	CAS No	Exposure route	ATE
phosphoric acid	7664-38-2	oral	1,530 mg/kg
phosphoric acid	7664-38-2	inhalation: vapor	0.5 mg/l/4h
phosphoric acid	7664-38-2	inhalation: dust/mist	0.2125 mg/l/4h
sulfuric acid ... %	7664-93-9	inhalation: vapor	3 mg/l/4h
sulfuric acid ... %	7664-93-9	inhalation: dust/mist	0.85 mg/l/4h
hydrofluoric acid ... %	7664-39-3	oral	50 mg/kg
hydrofluoric acid ... %	7664-39-3	dermal	5 mg/kg
hydrofluoric acid ... %	7664-39-3	inhalation: vapor	0.5 mg/l/4h
Alcohols, C9-11 ethoxylated	68439-46-3	oral	1,200 mg/kg
Alcohols, C9-11 ethoxylated	68439-46-3	dermal	2,000 mg/kg

Skin corrosion/irritation

Causes severe skin burns and eye damage.

Serious eye damage/eye irritation

Causes serious eye damage.

Respiratory or skin sensitization

Shall not be classified as a respiratory or skin sensitizer.

Germ cell mutagenicity

Shall not be classified as germ cell mutagenic.

Carcinogenicity

May cause cancer.

Wire Wheel Acid

Version number: GHS 2.0
Replaces version of: 2019-06-17 (GHS 1)

Revision: 2019-06-17

IARC Monographs on the Evaluation of Carcinogenic Risks to Humans

Name of substance	CAS No	Classification	Number
sulfuric acid ... %	7664-93-9	1	

Legend

1 Carcinogenic to humans

National Toxicology Program (United States): Report on Carcinogens

Name of substance	CAS No	Classification	Number
sulfuric acid ... %	7664-93-9	Known to be a human carcinogen	9th Report on Carcinogens

Reproductive toxicity

Shall not be classified as a reproductive toxicant.

Specific target organ toxicity - single exposure

Shall not be classified as a specific target organ toxicant (single exposure).

Specific target organ toxicity - repeated exposure

Shall not be classified as a specific target organ toxicant (repeated exposure).

Aspiration hazard

Shall not be classified as presenting an aspiration hazard.

SECTION 12: Ecological information

12.1 Toxicity

Toxic to aquatic life with long lasting effects.

Aquatic toxicity (acute) of components of the mixture

Name of substance	CAS No	Endpoint	Value	Species	Exposure time
phosphoric acid	7664-38-2	EC50	>100 mg/l	aquatic invertebrates	48 h
phosphoric acid	7664-38-2	ErC50	>100 mg/l	algae	72 h
sulfuric acid ... %	7664-93-9	EC50	>100 mg/l	aquatic invertebrates	48 h
sulfuric acid ... %	7664-93-9	ErC50	>100 mg/l	algae	72 h
hydrofluoric acid ... %	7664-39-3	EC50	48 mg/l	aquatic invertebrates	96 h
Alcohols, C9-11 ethoxylated	68439-46-3	LC50	8.5 mg/l	fathead minnow	96 h
Alcohols, C9-11 ethoxylated	68439-46-3	EC50	5.3 mg/l	daphnia magna	48 h
Alcohols, C9-11 ethoxylated	68439-46-3	ErC50	1 – 10 mg/l	algae	96 h

12.2 Persistence and degradability

Data are not available.



Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

Wire Wheel Acid

Version number: GHS 2.0
Replaces version of: 2019-06-17 (GHS 1)

Revision: 2019-06-17

12.3 Bioaccumulative potential

Data are not available.

12.4 Mobility in soil

Data are not available.

12.5 Results of PBT and vPvB assessment

Data are not available.

12.6 Other adverse effects

Endocrine disrupting potential

None of the ingredients are listed.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Sewage disposal-relevant information

Do not empty into drains. Avoid release to the environment. Refer to special instructions/safety data sheets.

Waste treatment of containers/packages

Only packagings which are approved (e.g. acc. to DOT) may be used. Completely emptied packages can be recycled. Handle contaminated packages in the same way as the substance itself.

Remarks

Please consider the relevant national or regional provisions. Waste shall be separated into the categories that can be handled separately by the local or national waste management facilities.

SECTION 14: Transport information

14.1	UN number	2922
14.2	UN proper shipping name	Corrosive liquid, toxic, n.o.s.
	Technical name (hazardous ingredients)	hydrofluoric acid ... %
14.3	Transport hazard class(es)	
	Class	8 (corrosive substances)
	Subsidiary risk(s)	6.1 (acute toxicity)
14.4	Packing group	II (substance presenting medium danger)
14.5	Environmental hazards	hazardous to the aquatic environment
	Environmentally hazardous substance (aquatic environment)	sulfuric acid ... %
14.6	Special precautions for user	
	There is no additional information.	
14.7	Transport in bulk according to Annex II of MARPOL and the IBC Code	
	The cargo is not intended to be carried in bulk.	

Information for each of the UN Model Regulations

Wire Wheel Acid

Version number: GHS 2.0
Replaces version of: 2019-06-17 (GHS 1)

Revision: 2019-06-17

Transport of dangerous goods by road or rail (49 CFR US DOT)

Index number	2922
Proper shipping name	Corrosive liquid, toxic, n.o.s.
- Particulars in the shipper's declaration	UN2922, Corrosive liquid, toxic, n.o.s., (hydrofluoric acid ... %, solution), 8 (6.1), II, environmentally hazardous
- Reportable quantity (RQ)	2,715 lbs (1,233 kg) (hydrofluoric acid ... %) (sulfuric acid ... %)
Class	8
Subsidiary risk(s)	6.1
Packing group	II
Danger label(s)	8+6.1, fish and tree



Environmental hazards	YES (hazardous to the aquatic environment)
Special provisions (SP)	B3, IB2, T7, TP2
ERG No	154

International Maritime Dangerous Goods Code (IMDG)

UN number	2922
Proper shipping name	CORROSIVE LIQUID, TOXIC, N.O.S.
Class	8
Subsidiary risk(s)	6.1
Marine pollutant	YES (hazardous to the aquatic environment)
Packing group	II
Danger label(s)	8+6.1, fish and tree



Special provisions (SP)	274
Excepted quantities (EQ)	E2
Limited quantities (LQ)	1 L
EmS	F-A, S-B
Stowage category	B

International Civil Aviation Organization (ICAO-IATA/DGR)

UN number	2922
Proper shipping name	Corrosive liquid, toxic, n.o.s.
Class	8
Subsidiary risk(s)	6.1
Environmental hazards	YES (hazardous to the aquatic environment)
Packing group	II
Danger label(s)	8+6.1

Wire Wheel Acid

Version number: GHS 2.0
Replaces version of: 2019-06-17 (GHS 1)

Revision: 2019-06-17



Special provisions (SP) A3
 Excepted quantities (EQ) E2
 Limited quantities (LQ) 0,5 L

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations specific for the product in question

National regulations (United States)

15.1.5 Toxic Substance Control Act (TSCA) all ingredients are listed
0.1

Superfund Amendment and Reauthorization Act (SARA TITLE III)

- The List of Extremely Hazardous Substances and Their Threshold Planning Quantities (EPCRA Section 302, 304)

The List of Extremely Hazardous Substances and Their Threshold Planning Quantities				
Name acc. to inventory	CAS No	Notes	Reportable quantity (pounds)	Threshold planning quantity (pounds)
hydrogen fluoride	7664-39-3		100	100
sulfuric acid	7664-93-9		1,000	1000

- Specific Toxic Chemical Listings (EPCRA Section 313)

Toxics Release Inventory: Specific Toxic Chemical Listings			
Name acc. to inventory	CAS No	Remarks	Effective date
hydrogen fluoride	7664-39-3		1986-12-31
sulfuric acid	7664-93-9	acid aerosols including mists, vapors, gas, fog, and other airborne forms of any particle size	1986-12-31

Comprehensive Environmental Response, Compensation, and Liability Act (CERCLA)

- List of Hazardous Substances and Reportable Quantities (CERCLA section 102a) (40 CFR 302.4)

Name of substance	CAS No	Remarks	Statutory code	Final RQ pounds (Kg)
hydrofluoric acid ... %	7664-39-3		1 3 4	100 (45,4)
phosphoric acid	7664-38-2		1	5000 (2270)
sulfuric acid ... %	7664-93-9		1	1000 (454)

Legend

1 "1" indicates that the statutory source is section 311(b)(2) of the Clean Water Act
 3 "3" indicates that the source is section 112 of the Clean Air Act
 4 "4" indicates that the source is section 3001 of the Resource Conservation and Recovery Act (RCRA)



Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

Wire Wheel Acid

Version number: GHS 2.0
Replaces version of: 2019-06-17 (GHS 1)

Revision: 2019-06-17

Clean Air Act

Name of substance	CAS No	Type of registration	Basis for listing	Threshold quantity (lbs)
hydrofluoric acid ... %	7664-39-3	Toxic substance	a b	1000

Legend

- A Mandated for listing by Congress.
- B On EHS list, vapor pressure 10 mmHg or greater.

15.1.5 New Jersey Worker and Community Right to Know Act 0.5

Right to Know Hazardous Substance List			
Name acc. to inventory	CAS No	Remarks	Classifications
hydrogen fluoride	7664-39-3		CO R1
phosphoric acid	7664-38-2		CO
SULFURIC ACID (DIHYDROGEN SULFATE)	7664-93-9		CA CO R2

Legend

- CA Carcinogenic
- CO Corrosive
- R1 Reactive - First Degree
- R2 Reactive - Second Degree

15.1.5 California Environmental Protection Agency (Cal/EPA): Proposition 65 - Safe Drinking Water and Toxic Enforcement Act of 1987 0.6

none of the ingredients are listed

Industry or sector specific available guidance(s)

NPCA-HMIS® III

Hazardous Materials Identification System. American Coatings Association.

Category	Rating	Description
Chronic	*	chronic (long-term) health effects may result from repeated overexposure
Health	3	major injury likely unless prompt action is taken and medical treatment is given
Flammability	0	material that will not burn under typical fire conditions
Physical hazard	0	material that is normally stable, even under fire conditions, and will not react with water, polymerize, decompose, condense, or self-react. Non-explosive
Personal protection	-	

- Chronic: chronic hazard
- Flammability: flammability hazard
- Health: health hazard
- Personal protection: personal protective equipment (PPE) for normal use
- Physical hazard: reactivity

NFPA® 704

National Fire Protection Association: Standard System for the Identification of the Hazards of Materials for Emergency Response (United States).



Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

Wire Wheel Acid

Version number: GHS 2.0
Replaces version of: 2019-06-17 (GHS 1)

Revision: 2019-06-17

Category	Degree of hazard	Description
Flammability	0	material that will not burn under typical fire conditions
Health	3	material that, under emergency conditions, can cause serious or permanent injury
Instability	0	material that is normally stable, even under fire conditions
Special hazard		

National inventories

Country	Inventory	Status
CA	DSL	all ingredients are listed
EU	REACH Reg.	all ingredients are listed
US	TSCA	all ingredients are listed

Legend

DSL Domestic Substances List (DSL)
REACH Reg. REACH registered substances
TSCA Toxic Substance Control Act

15.2 Chemical Safety Assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information, including date of preparation or last revision

Indication of changes (revised safety data sheet)

Section	Former entry (text/value)	Actual entry (text/value)	Safety-relevant
14.2		Technical name (hazardous ingredients): hydrofluoric acid ... %	yes
14.7	Particulars in the shipper's declaration: UN2922, Corrosive liquid, toxic, n.o.s., 8 (6.1), II, environmentally hazardous	Particulars in the shipper's declaration: UN2922, Corrosive liquid, toxic, n.o.s., (hydrofluoric acid ... %, solution), 8 (6.1), II, environmentally haz- ardous	yes

Abbreviations and acronyms

Abbr.	Descriptions of used abbreviations
29 CFR 1910.1000	29 CFR 1910.1000, Tables Z-1, Z-2, Z-3 - Occupational Safety and Health Standards: Toxic and Hazardous Substances (permissible exposure limits)
49 CFR US DOT	49 CFR § 40 U.S. Department of Transportation
Acute Tox.	Acute toxicity
ATE	Acute Toxicity Estimate
Cal/OSHA PEL	California Division of Occupational Safety and Health (Cal/OSHA): Permissible Exposure Limits (PELs)
Carc.	Carcinogenicity
CAS	Chemical Abstracts Service (service that maintains the most comprehensive list of chemical substances)
Ceiling-C	Ceiling value
DGR	Dangerous Goods Regulations (see IATA/DGR)



Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

Wire Wheel Acid

Version number: GHS 2.0
Replaces version of: 2019-06-17 (GHS 1)

Revision: 2019-06-17

Abbr.	Descriptions of used abbreviations
DNEL	Derived No-Effect Level
DOT	Department of Transportation (USA)
EmS	Emergency Schedule
ERG No	Emergency Response Guidebook - Number
Eye Dam.	Seriously damaging to the eye
Eye Irrit.	Irritant to the eye
GHS	"Globally Harmonized System of Classification and Labelling of Chemicals" developed by the United Nations
IARC	International Agency for Research on Cancer
IATA	International Air Transport Association
IATA/DGR	Dangerous Goods Regulations (DGR) for the air transport (IATA)
ICAO	International Civil Aviation Organization
IMDG	International Maritime Dangerous Goods Code
MARPOL	International Convention for the Prevention of Pollution from Ships (abbr. of "Marine Pollutant")
Met. Corr.	Substance or mixture corrosive to metals
NIOSH REL	National Institute for Occupational Safety and Health (NIOSH): Recommended Exposure Limits (RELs)
NPCA-HMIS® III	National Paint and Coatings Association: Hazardous Materials Identification System - HMIS® III, Third Edition
NTP-RoC	National Toxicology Program (United States): Report on Carcinogens
OSHA	Occupational Safety and Health Administration (United States)
PBT	Persistent, Bioaccumulative and Toxic
PEL	Permissible exposure limit
PNEC	Predicted No-Effect Concentration
ppm	Parts per million
Skin Corr.	Corrosive to skin
Skin Irrit.	Irritant to skin
STEL	Short-term exposure limit
TWA	Time-weighted average
vPvB	Very Persistent and very Bioaccumulative

Key literature references and sources for data

OSHA Hazard Communication Standard (HCS), 29 CFR 1910.1200.

Transport of dangerous goods by road or rail (49 CFR US DOT). International Maritime Dangerous Goods Code (IMDG). Dangerous Goods Regulations (DGR) for the air transport (IATA).

Classification procedure

Physical and chemical properties: The classification is based on tested mixture.

Health hazards, Environmental hazards: The method for classification of the mixture is based on ingredients of the mixture (additivity formula).



Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

Wire Wheel Acid

Version number: GHS 2.0
Replaces version of: 2019-06-17 (GHS 1)

Revision: 2019-06-17

List of relevant phrases (code and full text as stated in chapter 2 and 3)

Code	Text
H290	May be corrosive to metals.
H300	Fatal if swallowed.
H302	Harmful if swallowed.
H310	Fatal in contact with skin.
H312	Harmful in contact with skin.
H314	Causes severe skin burns and eye damage.
H318	Causes serious eye damage.
H330	Fatal if inhaled.
H331	Toxic if inhaled.
H350	May cause cancer.

Disclaimer

This information is based upon the present state of our knowledge. This SDS has been compiled and is solely intended for this product.