

Better Wax VOC

Version number: GHS 10.0
Replaces version of: 2018-10-02 (GHS 9)

Revision: 2019-06-13

SECTION 1: Identification

1.1 Product identifier

Trade name **Better Wax VOC**

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses Vehicle polish

1.3 Details of the supplier of the safety data sheet

B&B Blending, LLC
10963 Leroy Drive
Northglenn CO 80233
United States

Telephone: 1.800.875.6320, 1.303.289.6320

e-mail: info@bbblending.com

Website: bbblending.com

e-mail (competent person)

btirrell@bbblending.com

1.4 Emergency telephone number

Emergency information service

USA 1.800.535.5053, INTL 1.352.323.3500
24 hr emergency information

SECTION 2: Hazard(s) identification

2.1 Classification of the substance or mixture

Classification acc. to OSHA "Hazard Communication Standard" (29 CFR 1910.1200)

Section	Hazard class	Category	Hazard class and category	Hazard statement
A.2	skin corrosion/irritation	2	Skin Irrit. 2	H315
A.7	reproductive toxicity	2	Repr. 2	H361f
B.6	flammable liquid	4	Flam. Liq. 4	H227

For full text of abbreviations: see SECTION 16.

The most important adverse physicochemical, human health and environmental effects

The product is combustible and can be ignited by potential ignition sources. The mixture contains a substance that was identified as a PBT (persistent, bioaccumulative and toxic). The mixture contains a substance that was identified as vPvB (very persistent and very bioaccumulative).

Additional information

Containing a PBT-/vPvB-substance in a concentration of $\geq 0,1\%$.

2.2 Label elements

Labelling acc. to OSHA "Hazard Communication Standard" (29 CFR 1910.1200)

- Signal word warning

- Pictograms

GHS07, GHS08





Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

Better Wax VOC

Version number: GHS 10.0
Replaces version of: 2018-10-02 (GHS 9)

Revision: 2019-06-13

- Hazard statements

H227 Combustible liquid.
H315 Causes skin irritation.
H361f Suspected of damaging fertility.

- Precautionary statements

P201 Obtain special instructions before use.
P202 Do not handle until all safety precautions have been read and understood.
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P280 Wear protective gloves/protective clothing/eye protection/face protection.
P281 Wear personal protective equipment/face protection.
P302+P352 If on skin: Wash with plenty of water.
P308+P313 If exposed or concerned: Get medical advice/attention.
P321 Specific treatment (see on this label).
P332+P313 If skin irritation occurs: Get medical advice/attention.
P362 Take off contaminated clothing and wash it before reuse.
P370+P378 In case of fire: Use sand, carbon dioxide or powder extinguisher to extinguish.
P403+P235 Store in a well-ventilated place. Keep cool.
P405 Store locked up.
P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

- Hazardous ingredients for labelling octamethylcyclotetrasiloxane

2.3 Other hazards

This material is combustible, but will not ignite readily. Special danger of slipping by leaking/spilling product.

Hazards not otherwise classified

Very toxic to aquatic life with long lasting effects (GHS category 1: aquatic toxicity - acute and/or chronic).

SECTION 3: Composition/information on ingredients

3.1 Substances

Not relevant (mixture)

3.2 Mixtures

Description of the mixture

Hazardous ingredients acc. to GHS				
Name of substance	Identifier	Wt%	Classification acc. to GHS	Notes
odorless mineral spirits	CAS No 64742-48-9	12 - < 20	Skin Irrit. 2 / H315 STOT SE 3 / H336 Asp. Tox. 1 / H304 Flam. Liq. 3 / H226	
China Clay, calcined	CAS No 66402-68-4	3 - < 12	Acute Tox. 4 / H332	
octamethylcyclotetrasiloxane	CAS No 556-67-2	1 - < 3	Repr. 2 / H361f Flam. Liq. 3 / H226	PBT vPvB
decamethylcyclopentasiloxane	CAS No 541-02-6	0.1 - < 1	Flam. Liq. 4 / H227	PBT vPvB
ethyl alcohol	CAS No 64-17-5	0.1 - < 1	Eye Irrit. 2 / H319 Carc. 1A / H350 Flam. Liq. 2 / H225	* IARC: 1

Notes

*: only carcinogenic in alcoholic beverages



Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

Better Wax VOC

Version number: GHS 10.0
Replaces version of: 2018-10-02 (GHS 9)

Revision: 2019-06-13

Notes

IARC: 1: IARC group 1: carcinogenic to humans (International Agency for Research on Cancer)

PBT: The substance was identified as a PBT (persistent, bioaccumulative and toxic)

vPvB: The substance was identified as a vPvB (very persistent and very bioaccumulative)

For full text of abbreviations: see SECTION 16. Exact percentage of ingredients is withheld as a trade secret.

SECTION 4: First-aid measures

4.1 Description of first-aid measures

General notes

Do not leave affected person unattended. Remove victim out of the danger area. Keep affected person warm, still and covered. Take off immediately all contaminated clothing. In all cases of doubt, or when symptoms persist, seek medical advice. In case of unconsciousness place person in the recovery position. Never give anything by mouth.

Following inhalation

If breathing is irregular or stopped, immediately seek medical assistance and start first aid actions. In case of respiratory tract irritation, consult a physician. Provide fresh air.

Following skin contact

Wash with plenty of soap and water.

Following eye contact

Remove contact lenses, if present and easy to do. Continue rinsing.

Following ingestion

Rinse mouth with water (only if the person is conscious). Do NOT induce vomiting.

SECTION 5: Fire-fighting measures

5.1 Extinguishing media

Suitable extinguishing media

Water spray, BC-powder, Carbon dioxide (CO₂)

Unsuitable extinguishing media

Water jet

5.2 Special hazards arising from the substance or mixture

In case of insufficient ventilation and/or in use, may form flammable/explosive vapor-air mixture. Solvent vapors are heavier than air and may spread along floors. Places which are not ventilated, e.g. unventilated below ground level areas such as trenches, conduits and shafts, are particularly prone to the presence of flammable substances or mixtures.

Hazardous combustion products

Nitrogen oxides (NO_x), Carbon monoxide (CO), Carbon dioxide (CO₂)

5.3 Advice for firefighters

In case of fire and/or explosion do not breathe fumes. Co-ordinate firefighting measures to the fire surroundings. Do not allow firefighting water to enter drains or water courses. Collect contaminated firefighting water separately. Fight fire with normal precautions from a reasonable distance.

Better Wax VOC

Version number: GHS 10.0
Replaces version of: 2018-10-02 (GHS 9)

Revision: 2019-06-13

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

Remove persons to safety.

For emergency responders

Wear breathing apparatus if exposed to vapors/dust/aerosols/gases.

6.2 Environmental precautions

Keep away from drains, surface and ground water. Retain contaminated washing water and dispose of it. If substance has entered a water course or sewer, inform the responsible authority.

6.3 Methods and material for containment and cleaning up

Advices on how to contain a spill

Covering of drains

Advices on how to clean up a spill

Wipe up with absorbent material (e.g. cloth, fleece). Collect spillage: sawdust, kieselgur (diatomite), sand, universal binder

Appropriate containment techniques

Use of adsorbent materials.

Other information relating to spills and releases

Place in appropriate containers for disposal. Ventilate affected area.

6.4 Reference to other sections

Hazardous combustion products: see section 5. Personal protective equipment: see section 8. Incompatible materials: see section 10. Disposal considerations: see section 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Recommendations

- Measures to prevent fire as well as aerosol and dust generation

Use local and general ventilation. Avoidance of ignition sources. Keep away from sources of ignition - No smoking. Take precautionary measures against static discharge. Use only in well-ventilated areas. Due to danger of explosion, prevent leakage of vapours into cellars, flues and ditches. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting/equipment. Use only non-sparking tools.

- Specific notes/details

Places which are not ventilated, e.g. unventilated below ground level areas such as trenches, conduits and shafts, are particularly prone to the presence of flammable substances or mixtures. Vapors are heavier than air, spread along floors and form explosive mixtures with air. Vapors may form explosive mixtures with air.

Advice on general occupational hygiene

Wash hands after use. Do not eat, drink and smoke in work areas. Remove contaminated clothing and protective equipment before entering eating areas. Never keep food or drink in the vicinity of chemicals. Never place chemicals in containers that are normally used for food or drink. Keep away from food, drink and animal feedingstuffs.

7.2 Conditions for safe storage, including any incompatibilities

Managing of associated risks

- Explosive atmospheres

Keep container tightly closed and in a well-ventilated place. Use local and general ventilation. Keep cool. Protect from sunlight.

Better Wax VOC

Version number: GHS 10.0
Replaces version of: 2018-10-02 (GHS 9)

Revision: 2019-06-13

- Flammability hazards

Keep away from sources of ignition - No smoking. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Take precautionary measures against static discharge. Protect from sunlight.

Control of the effects

Protect against external exposure, such as

Frost

- Ventilation requirements

Use local and general ventilation. Ground/bond container and receiving equipment.

- Packaging compatibilities

Only packagings which are approved (e.g. acc. to the Dangerous Goods Regulations) may be used.

7.3 Specific end use(s)

See section 16 for a general overview.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limit values (Workplace Exposure Limits)											
Country	Name of agent	CAS No	Identifier	TWA [ppm]	TWA [mg/m ³]	STEL [ppm]	STEL [mg/m ³]	Ceiling-C [ppm]	Ceiling-C [mg/m ³]	Notation	Source
US	ethyl alcohol (ethanol)	64-17-5	PEL	1,000	1,900						29 CFR 1910.1000
US	petroleum distillates (naphtha) (rubber solvent)	64742-48-9	PEL	500	2,000						29 CFR 1910.1000

Notation

Ceiling-C
STEL

ceiling value is a limit value above which exposure should not occur
short-term exposure limit: a limit value above which exposure should not occur and which is related to a 15-minute period (unless otherwise specified)

TWA

time-weighted average (long-term exposure limit): measured or calculated in relation to a reference period of 8 hours time-weighted average (unless otherwise specified)

Relevant DNELs of components of the mixture						
Name of substance	CAS No	End-point	Threshold level	Protection goal, route of exposure	Used in	Exposure time
China Clay, calcined	66402-68-4	DNEL	15.63 mg/m ³	human, inhalatory	worker (industry)	chronic - local effects
octamethylcyclotetrasiloxane	556-67-2	DNEL	73 mg/m ³	human, inhalatory	worker (industry)	chronic - systemic effects
octamethylcyclotetrasiloxane	556-67-2	DNEL	73 mg/m ³	human, inhalatory	worker (industry)	acute - systemic effects
octamethylcyclotetrasiloxane	556-67-2	DNEL	73 mg/m ³	human, inhalatory	worker (industry)	chronic - local effects



Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

Better Wax VOC

Version number: GHS 10.0
Replaces version of: 2018-10-02 (GHS 9)

Revision: 2019-06-13

Relevant DNELs of components of the mixture

Name of substance	CAS No	End-point	Threshold level	Protection goal, route of exposure	Used in	Exposure time
octamethylcyclotetrasiloxane	556-67-2	DNEL	73 mg/m ³	human, inhalatory	worker (industry)	acute - local effects
decamethylcyclopentasiloxane	541-02-6	DNEL	97.3 mg/m ³	human, inhalatory	worker (industry)	chronic - systemic effects
decamethylcyclopentasiloxane	541-02-6	DNEL	97.3 mg/m ³	human, inhalatory	worker (industry)	acute - systemic effects
decamethylcyclopentasiloxane	541-02-6	DNEL	24.2 mg/m ³	human, inhalatory	worker (industry)	chronic - local effects
decamethylcyclopentasiloxane	541-02-6	DNEL	24.2 mg/m ³	human, inhalatory	worker (industry)	acute - local effects
ethyl alcohol	64-17-5	DNEL	343 mg/kg	human, dermal	worker (industry)	chronic - systemic effects
ethyl alcohol	64-17-5	DNEL	950 mg/m ³	human, inhalatory	worker (industry)	chronic - systemic effects

Relevant PNECs of components of the mixture

Name of substance	CAS No	End-point	Threshold level	Organism	Environmental compartment	Exposure time
octamethylcyclotetrasiloxane	556-67-2	PNEC	10 mg/l	microorganisms	sewage treatment plant (STP)	short-term (single instance)
octamethylcyclotetrasiloxane	556-67-2	PNEC	0.059 mg/kg	pelagic organisms	sediment	short-term (single instance)
octamethylcyclotetrasiloxane	556-67-2	PNEC	1.7 mg/kg	(top) predators	water	short-term (single instance)
octamethylcyclotetrasiloxane	556-67-2	PNEC	0.44 µg/l	aquatic organisms	freshwater	short-term (single instance)
octamethylcyclotetrasiloxane	556-67-2	PNEC	0.044 µg/l	aquatic organisms	marine water	short-term (single instance)
octamethylcyclotetrasiloxane	556-67-2	PNEC	10 mg/l	aquatic organisms	sewage treatment plant (STP)	short-term (single instance)
octamethylcyclotetrasiloxane	556-67-2	PNEC	3 mg/kg	aquatic organisms	freshwater sediment	short-term (single instance)
octamethylcyclotetrasiloxane	556-67-2	PNEC	0.3 mg/kg	aquatic organisms	marine sediment	short-term (single instance)
octamethylcyclotetrasiloxane	556-67-2	PNEC	0.59 mg/kg	benthic organisms	sediment	short-term (single instance)
octamethylcyclotetrasiloxane	556-67-2	PNEC	0.16 mg/kg	terrestrial organisms	soil	short-term (single instance)
decamethylcyclopentasiloxane	541-02-6	PNEC	10 mg/l	microorganisms	sewage treatment plant (STP)	short-term (single instance)
decamethylcyclopentasiloxane	541-02-6	PNEC	11 mg/kg	benthic organisms	sediment	short-term (single instance)
decamethylcyclopentasiloxane	541-02-6	PNEC	13 mg/kg	(top) predators	water	short-term (single instance)

Better Wax VOC

Version number: GHS 10.0
Replaces version of: 2018-10-02 (GHS 9)

Revision: 2019-06-13

Relevant PNECs of components of the mixture						
Name of substance	CAS No	End-point	Threshold level	Organism	Environmental compartment	Exposure time
decamethylcyclopentasiloxane	541-02-6	PNEC	1.1 mg/kg	pelagic organisms	sediment	short-term (single instance)
decamethylcyclopentasiloxane	541-02-6	PNEC	1.2 µg/l	aquatic organisms	freshwater	short-term (single instance)
decamethylcyclopentasiloxane	541-02-6	PNEC	0.12 µg/l	aquatic organisms	marine water	short-term (single instance)
decamethylcyclopentasiloxane	541-02-6	PNEC	10 mg/l	aquatic organisms	sewage treatment plant (STP)	short-term (single instance)
decamethylcyclopentasiloxane	541-02-6	PNEC	11 mg/kg	aquatic organisms	freshwater sediment	short-term (single instance)
decamethylcyclopentasiloxane	541-02-6	PNEC	1.1 mg/kg	aquatic organisms	marine sediment	short-term (single instance)
decamethylcyclopentasiloxane	541-02-6	PNEC	1.27 mg/kg	terrestrial organisms	soil	short-term (single instance)
ethyl alcohol	64-17-5	PNEC	0.96 mg/l	aquatic organisms	freshwater	short-term (single instance)
ethyl alcohol	64-17-5	PNEC	0.79 mg/l	aquatic organisms	marine water	short-term (single instance)
ethyl alcohol	64-17-5	PNEC	580 mg/l	microorganisms	sewage treatment plant (STP)	short-term (single instance)
ethyl alcohol	64-17-5	PNEC	3.6 mg/kg	benthic organisms	sediment	short-term (single instance)
ethyl alcohol	64-17-5	PNEC	0.63 mg/kg	terrestrial organisms	soil	short-term (single instance)
ethyl alcohol	64-17-5	PNEC	2.75 mg/l	aquatic organisms	water	intermittent release

8.2 Exposure controls

Appropriate engineering controls

General ventilation.

Individual protection measures (personal protective equipment)

Eye/face protection

Wear eye/face protection.

Skin protection

- Hand protection

Wear suitable gloves. Chemical protection gloves are suitable, which are tested according to EN 374. Check leak-tightness/impermeability prior to use. In the case of wanting to use the gloves again, clean them before taking off and air them well. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

- Other protection measures

Take recovery periods for skin regeneration. Preventive skin protection (barrier creams/ointments) is recommended. Wash hands thoroughly after handling.

Respiratory protection

In case of inadequate ventilation wear respiratory protection.



Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

Better Wax VOC

Version number: GHS 10.0
Replaces version of: 2018-10-02 (GHS 9)

Revision: 2019-06-13

Environmental exposure controls

Use appropriate container to avoid environmental contamination. Keep away from drains, surface and ground water.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance

Physical state	liquid (viscous)
Color	light yellow
Odor	fruity

Other safety parameters

pH (value)	not determined
Melting point/freezing point	not determined
Initial boiling point and boiling range	83 – 100 °C at 101.3 kPa
Flash point	63 °C at 101.3 kPa 146 °F at 1 atm
Evaporation rate	not determined
Flammability (solid, gas)	not relevant, (fluid)

Explosive limits

- Lower explosion limit (LEL)	0.7 vol%
- Upper explosion limit (UEL)	5.4 vol%

Vapor pressure	31.69 hPa at 25 °C
Density	not determined
Vapor density	this information is not available
Relative density	1 at 25 °C (water = 1)
Solubility(ies)	not determined

Partition coefficient

- n-octanol/water (log KOW)	this information is not available
-----------------------------	-----------------------------------

Auto-ignition temperature	343 °C
---------------------------	--------

Viscosity

- Kinematic viscosity	5,000 cSt
-----------------------	-----------



Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

Better Wax VOC

Version number: GHS 10.0
Replaces version of: 2018-10-02 (GHS 9)

Revision: 2019-06-13

Explosive properties	none
Oxidizing properties	none

9.2 Other information

Temperature class (USA, acc. to NEC 500)	T2 (maximum permissible surface temperature on the equipment: 300 °C)
--	---

SECTION 10: Stability and reactivity

10.1 Reactivity

Concerning incompatibility: see below "Conditions to avoid" and "Incompatible materials". The mixture contains reactive substance(s). Risk of ignition.

If heated:

Risk of ignition

10.2 Chemical stability

See below "Conditions to avoid".

10.3 Possibility of hazardous reactions

No known hazardous reactions.

10.4 Conditions to avoid

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Hints to prevent fire or explosion

Use explosion-proof electrical/ventilating/lighting/equipment. Use only non-sparking tools. Take precautionary measures against static discharge.

10.5 Incompatible materials

Oxidizers

10.6 Hazardous decomposition products

Reasonably anticipated hazardous decomposition products produced as a result of use, storage, spill and heating are not known. Hazardous combustion products: see section 5.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Test data are not available for the complete mixture.

Classification procedure

The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

Classification acc. to OSHA "Hazard Communication Standard" (29 CFR 1910.1200)

Acute toxicity

Shall not be classified as acutely toxic.

Acute toxicity estimate (ATE) of components of the mixture			
Name of substance	CAS No	Exposure route	ATE
China Clay, calcined	66402-68-4	inhalation: dust/mist	2.3 mg _i /4h



Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

Better Wax VOC

Version number: GHS 10.0
Replaces version of: 2018-10-02 (GHS 9)

Revision: 2019-06-13

Skin corrosion/irritation

Causes skin irritation.

Serious eye damage/eye irritation

Shall not be classified as seriously damaging to the eye or eye irritant.

Respiratory or skin sensitization

Shall not be classified as a respiratory or skin sensitizer.

Germ cell mutagenicity

Shall not be classified as germ cell mutagenic.

Carcinogenicity

Shall not be classified as carcinogenic.

IARC Monographs on the Evaluation of Carcinogenic Risks to Humans

Name of substance	CAS No	Classification	Number
ethyl alcohol	64-17-5	1	

Legend

1 Carcinogenic to humans

Reproductive toxicity

Suspected of damaging fertility.

Specific target organ toxicity - single exposure

Shall not be classified as a specific target organ toxicant (single exposure).

Specific target organ toxicity - repeated exposure

Shall not be classified as a specific target organ toxicant (repeated exposure).

Aspiration hazard

Shall not be classified as presenting an aspiration hazard.

SECTION 12: Ecological information

12.1 Toxicity

Very toxic to aquatic life with long lasting effects.

Aquatic toxicity (acute) of components of the mixture					
Name of substance	CAS No	Endpoint	Value	Species	Exposure time
octamethylcyclotetrasiloxane	556-67-2	LC50	>22 µg/l	fish	96 h
octamethylcyclotetrasiloxane	556-67-2	EC50	>1,000 mg/l	aquatic invertebrates	96 h
decamethylcyclopentasiloxane	541-02-6	LC50	>16 µg/l	fish	96 h
decamethylcyclopentasiloxane	541-02-6	EC50	>2.9 µg/l	aquatic invertebrates	48 h
ethyl alcohol	64-17-5	LC50	14.2 g/l	fish	96 h
ethyl alcohol	64-17-5	EC50	12.9 g/l	fish	96 h

Better Wax VOC

Version number: GHS 10.0
Replaces version of: 2018-10-02 (GHS 9)

Revision: 2019-06-13

Aquatic toxicity (chronic) of components of the mixture					
Name of substance	CAS No	Endpoint	Value	Species	Exposure time
odorless mineral spirits	64742-48-9	EC50	15.41 mg/l	microorganisms	40 h
China Clay, calcined	66402-68-4	EC50	300.4 mg/l	microorganisms	3 h
octamethylcyclotetrasiloxane	556-67-2	LC50	10 µg/l	fish	14 d
octamethylcyclotetrasiloxane	556-67-2	EC50	>500 mg/l	aquatic invertebrates	24 h
decamethylcyclopentasiloxane	541-02-6	LC50	>16 µg/l	fish	14 d
decamethylcyclopentasiloxane	541-02-6	EC50	>15 µg/l	aquatic invertebrates	21 d
ethyl alcohol	64-17-5	LC50	>0.08 mg/l	fish	42 d
ethyl alcohol	64-17-5	EC50	22.6 g/l	algae	10 d
ethyl alcohol	64-17-5	ErC50	675 mg/l	algae	4 d

12.2 Persistence and degradability

Data are not available.

12.3 Bioaccumulative potential

The substance fulfills the very bioaccumulative criterion.

12.4 Mobility in soil

Data are not available.

12.5 Results of PBT and vPvB assessment

The mixture contains a substance that was identified as a PBT (persistent, bioaccumulative and toxic). The mixture contains a substance that was identified as vPvB (very persistent and very bioaccumulative).

12.6 Other adverse effects

Endocrine disrupting potential

The mixture contains substance(s) with an endocrine disrupting potential.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Waste treatment-relevant information

Solvent reclamation/regeneration.

Sewage disposal-relevant information

Do not empty into drains. Avoid release to the environment. Refer to special instructions/safety data sheets.

Waste treatment of containers/packages

Only packagings which are approved (e.g. acc. to DOT) may be used. Completely emptied packages can be recycled. Handle contaminated packages in the same way as the substance itself.

Remarks

Please consider the relevant national or regional provisions. Waste shall be separated into the categories that can be handled separately by the local or national waste management facilities.

Better Wax VOC

Version number: GHS 10.0
Replaces version of: 2018-10-02 (GHS 9)

Revision: 2019-06-13


SECTION 14: Transport information

14.1 UN number	3082
14.2 UN proper shipping name	Environmentally hazardous substance, liquid, n.o.s.
14.3 Transport hazard class(es)	
Class	9 (environmentally hazardous)
14.4 Packing group	III (substance presenting low danger)
14.5 Environmental hazards	hazardous to the aquatic environment
14.6 Special precautions for user	
There is no additional information.	
14.7 Transport in bulk according to Annex II of MARPOL and the IBC Code	
The cargo is not intended to be carried in bulk.	

Information for each of the UN Model Regulations

Transport of dangerous goods by road or rail (49 CFR US DOT)

Not regulated under DOT until packaged in single containers larger than 119 gallons each - liquid, or 882 lbs each - solid.

Index number	3082
Proper shipping name	Environmentally hazardous substance, liquid, n.o.s.
- Particulars in the shipper's declaration	UN3082, Environmentally hazardous substance, liquid, n.o.s., 9, III
- Reportable quantity (RQ)	121,828,571 lbs (55,310,171 kg) (amyl acetate) (4-methylpentan-2-one)
Class	9
Packing group	III
Danger label(s)	9, fish and tree
	
Environmental hazards	yes (hazardous to the aquatic environment)
Special provisions (SP)	8, 146, 173, 335, IB3, T4, TP1, TP29
ERG No	171

International Maritime Dangerous Goods Code (IMDG)


UN number	3082
Proper shipping name	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.
Class	9
Marine pollutant	yes (hazardous to the aquatic environment)
Packing group	III
Danger label(s)	9, fish and tree



Better Wax VOC

Version number: GHS 10.0
Replaces version of: 2018-10-02 (GHS 9)

Revision: 2019-06-13

Special provisions (SP)	274, 335, 969
Excepted quantities (EQ)	E1
Limited quantities (LQ)	5 L
EmS	F-A, S-F
Stowage category	A
International Civil Aviation Organization (ICAO-IATA/DGR)	
UN number	3082
Proper shipping name	Environmentally hazardous substance, liquid, n.o.s.
Class	9
Environmental hazards	yes (hazardous to the aquatic environment)
Packing group	III
Danger label(s)	9, fish and tree
	
Special provisions (SP)	A97, A158, A197
Excepted quantities (EQ)	E1
Limited quantities (LQ)	30 kg

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations specific for the product in question

National regulations (United States)

15.1.5 **Toxic Substance Control Act (TSCA)** all ingredients are listed
0.1

Superfund Amendment and Reauthorization Act (SARA TITLE III)

- The List of Extremely Hazardous Substances and Their Threshold Planning Quantities (EPCRA Section 302, 304)

none of the ingredients are listed

Clean Air Act

none of the ingredients are listed

15.1.5 **New Jersey Worker and Community Right to Know Act**
0.5

Right to Know Hazardous Substance List			
Name acc. to inventory	CAS No	Remarks	Classifications
ethyl alcohol	64-17-5		CA MU TE F3

Legend

CA Carcinogenic
F3 Flammable - Third Degree
MU Mutagenic
TE Teratogenic



Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

Better Wax VOC

Version number: GHS 10.0
Replaces version of: 2018-10-02 (GHS 9)

Revision: 2019-06-13

15.1.5 California Environmental Protection Agency (Cal/EPA): Proposition 65 - Safe Drinking Water and Toxic Enforcement Act of 1987

Proposition 65 List of chemicals				
Name acc. to inventory	CAS No	Conc.	Remarks	Type of the toxicity
ethanol (ethyl alcohol)	64-17-5	0.1157 wt%	in alcoholic beverages	developmental
methyl isobutyl ketone	108-10-1	0.0013 wt%		cancer
methyl isobutyl ketone (MIBK)	108-10-1	0.0013 wt%		developmental

Industry or sector specific available guidance(s)

NPCA-HMIS® III

Hazardous Materials Identification System. American Coatings Association.

Category	Rating	Description
Chronic	*	chronic (long-term) health effects may result from repeated overexposure
Health	2	temporary or minor injury may occur
Flammability	2	material that must be moderately heated or exposed to relatively high ambient temperatures before ignition can occur
Physical hazard	0	material that is normally stable, even under fire conditions, and will not react with water, polymerize, decompose, condense, or self-react. Non-explosive
Personal protection	-	

Chronic: chronic hazard
 Flammability: flammability hazard
 Health: health hazard
 Personal protection: personal protective equipment (PPE) for normal use
 Physical hazard: reactivity

NFPA® 704

National Fire Protection Association: Standard System for the Identification of the Hazards of Materials for Emergency Response (United States).

Category	Degree of hazard	Description
Flammability	2	material that must be moderately heated or exposed to relatively high ambient temperatures before ignition can occur
Health	2	material that, under emergency conditions, can cause temporary incapacitation or residual injury
Instability	0	material that is normally stable, even under fire conditions
Special hazard		

National inventories



Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

Better Wax VOC

Version number: GHS 10.0
Replaces version of: 2018-10-02 (GHS 9)

Revision: 2019-06-13

Country	Inventory	Status
CA	DSL	all ingredients are listed
EU	REACH Reg.	not all ingredients are listed
US	TSCA	all ingredients are listed

Legend

DSL Domestic Substances List (DSL)
REACH Reg. REACH registered substances
TSCA Toxic Substance Control Act

15.2 Chemical Safety Assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information, including date of preparation or last revision

Indication of changes (revised safety data sheet)

Section	Former entry (text/value)	Actual entry (text/value)	Safety-relevant
1.2	Uses advised against: do not use for products which come into contact with the food stuffs		yes
1.3	Details of the supplier of the safety data sheet: B&B Blending, LLC 10963 Leroy Drive Northglenn CO 80233 United States Telephone: 1.800.875.6320, 1.303.289.6320 Telefax e-mail: info@bbblending.com Website: bbblending.com	Details of the supplier of the safety data sheet: B&B Blending, LLC 10963 Leroy Drive Northglenn CO 80233 United States Telephone: 1.800.875.6320, 1.303.289.6320 e-mail: info@bbblending.com Website: bbblending.com	yes
1.3	Competent person responsible for the SDS: Beth Tirrell		yes
1.3	e-mail (competent person): btirrell@bbblending.com		yes
1.3		e-mail (competent person): btirrell@bbblending.com	yes
1.4	Emergency information service: USA 1.800.535.5053, INTL 1.352.323.3500 24 hour emergency telephone number.	Emergency information service: USA 1.800.535.5053, INTL 1.352.323.3500 24 hr emergency information	yes
2.1	Classification acc. to OSHA "Hazard Communication Standard" (29 CFR 1910.1200): Annex - Hazard class and category - Hazard statement code(s)	Classification acc. to OSHA "Hazard Communication Standard" (29 CFR 1910.1200)	yes
2.1		Classification acc. to OSHA "Hazard Communication Standard" (29 CFR 1910.1200): change in the listing (table)	yes
2.1	Remarks: For full text of H-phrases: see SECTION 16.		yes
2.1	Hazards not otherwise classified		yes
2.1		Hazards not otherwise classified: change in the listing (table)	yes



Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

Better Wax VOC

Version number: GHS 10.0
Replaces version of: 2018-10-02 (GHS 9)

Revision: 2019-06-13

Section	Former entry (text/value)	Actual entry (text/value)	Safety-relevant
2.1		Additional information: Containing a PBT-/vPvB-substance in a concentration of $\geq 0,1\%$.	yes
2.2	Signal word: danger	- Signal word: warning	yes
2.2		Pictograms: change in the listing (table)	yes
2.2	Hazard statements		yes
2.2		- Pictograms: change in the listing (table)	yes
2.2		- Hazard statements: change in the listing (table)	yes
2.2	Precautionary statements		yes
2.2	Precautionary statements - prevention		yes
2.2		Precautionary statements - prevention: change in the listing (table)	yes
2.2	Precautionary statements - response		yes
2.2		Precautionary statements - response: change in the listing (table)	yes
2.2	Precautionary statements - storage		yes
2.2		Precautionary statements - storage: change in the listing (table)	yes
2.2	Precautionary statements - disposal		yes
2.2		Precautionary statements - disposal: change in the listing (table)	yes
2.2		- Precautionary statements: change in the listing (table)	yes
2.2		- Hazardous ingredients for labelling: octamethylcyclotetrasiloxane	yes
2.3		Hazards not otherwise classified	yes
2.3		Hazards not otherwise classified: change in the listing (table)	yes
3.2		Description of the mixture: change in the listing (table)	yes
3.2		Hazardous ingredients acc. to GHS: change in the listing (table)	yes
4.1	Following inhalation: In case of respiratory tract irritation, consult a physician. Provide fresh air.	Following inhalation: If breathing is irregular or stopped, immediately seek medical assistance and start first aid actions. In case of respiratory tract irritation, consult a physician. Provide fresh air.	yes
4.1	Following skin contact: After contact with skin, take off immediately all contaminated clothing, and wash immediately with plenty of water.	Following skin contact: Wash with plenty of soap and water.	yes



Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

Better Wax VOC

Version number: GHS 10.0
Replaces version of: 2018-10-02 (GHS 9)

Revision: 2019-06-13

Section	Former entry (text/value)	Actual entry (text/value)	Safety-relevant
4.1	Following eye contact: Irrigate copiously with clean, fresh water, holding the eyelids apart. Remove contact lenses, if present and easy to do. Continue rinsing.	Following eye contact: Remove contact lenses, if present and easy to do. Continue rinsing.	yes
5.2	Hazardous combustion products: nitrogen oxides (NOx)	Hazardous combustion products: Nitrogen oxides (NOx), Carbon monoxide (CO), Carbon dioxide (CO2)	yes
6.2	Environmental precautions: Keep away from drains, surface and ground water. Retain contaminated washing water and dispose of it.	Environmental precautions: Keep away from drains, surface and ground water. Retain contaminated washing water and dispose of it. If substance has entered a water course or sewer, inform the responsible authority.	yes
7.2	Incompatible substances or mixtures: Observe compatible storage of chemicals.		yes
7.2	Consideration of other advice		yes
7.2		- Packaging compatibilities: Only packagings which are approved (e.g. acc. to the Dangerous Goods Regulations) may be used.	yes
8.1	National limit values		yes
8.1	Occupational exposure limit values (Workplace Exposure Limits)		yes
8.1	Relevant DNELs/DMELs/PNECs and other threshold levels: No data available.		yes
8.1		Relevant DNELs of components of the mixture: change in the listing (table)	yes
8.1		Relevant PNECs of components of the mixture: change in the listing (table)	yes
9.1	Odor: fruity		yes
9.1		Odor: fruity	yes
9.1	Flash point: 63 °C at 101.3 kPa 146 °F at 1 atm (closed cup)	Flash point: 63 °C at 101.3 kPa 146 °F at 1 atm	yes
9.1	Vapor pressure: 132 Pa at 25 °C	Vapor pressure: 31.69 hPa at 25 °C	yes
9.1		Vapor density: this information is not available	yes
9.1	Viscosity: not determined	Viscosity	yes
9.1		Kinematic viscosity: 5,000 cSt	yes
9.1	Oxidizing properties: none There is no additional information.	Oxidizing properties: none	yes
9.2		Other information	yes
9.2		Temperature class (USA, acc. to NEC 500): T2 (maximum permissible surface temperature on the equipment: 300 °C)	yes



Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

Better Wax VOC

Version number: GHS 10.0
Replaces version of: 2018-10-02 (GHS 9)

Revision: 2019-06-13

Section	Former entry (text/value)	Actual entry (text/value)	Safety-relevant
10.4	Physical stresses which might result in a hazardous situation and have to be avoided: strong shocks		yes
11.1	Acute toxicity of components of the mixture		yes
11.1		Acute toxicity estimate (ATE) of components of the mixture: change in the listing (table)	yes
11.1	Summary of evaluation of the CMR properties: Shall not be classified as germ cell mutagenic, carcinogenic nor as a reproductive toxicant.		yes
11.1	Carcinogenicity		yes
11.1	• National Toxicology Program (United States): none of the ingredients are listed		yes
11.1	• IARC Monographs		yes
11.1	Specific target organ toxicity (STOT): Shall not be classified as a specific target organ toxicant.		yes
11.1		Germ cell mutagenicity: Shall not be classified as germ cell mutagenic.	yes
11.1		Carcinogenicity: Shall not be classified as carcinogenic.	yes
11.1		IARC Monographs on the Evaluation of Carcinogenic Risks to Humans: change in the listing (table)	yes
11.1		Reproductive toxicity: Suspected of damaging fertility.	yes
11.1		Specific target organ toxicity - single exposure: Shall not be classified as a specific target organ toxicant (single exposure).	yes
11.1		Specific target organ toxicity - repeated exposure: Shall not be classified as a specific target organ toxicant (repeated exposure).	yes
11.1	Aspiration hazard: May be fatal if swallowed and enters airways.	Aspiration hazard: Shall not be classified as presenting an aspiration hazard.	yes
12.1	Aquatic toxicity (acute): Shall not be classified as hazardous to the aquatic environment.		yes
12.1	Aquatic toxicity (acute) of components of the mixture		yes
12.1	Aquatic toxicity (chronic)		yes
12.1	Aquatic toxicity (chronic) of components of the mixture		yes
12.2	Persistence and degradability	Persistence and degradability: Data are not available.	yes
12.2	Degradability of components of the mixture		yes
12.2		Degradability of components of the mixture: change in the listing (table)	yes



Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

Better Wax VOC

Version number: GHS 10.0
Replaces version of: 2018-10-02 (GHS 9)

Revision: 2019-06-13

Section	Former entry (text/value)	Actual entry (text/value)	Safety-relevant
12.3	Bioaccumulative potential of components of the mixture		yes
12.3		Bioaccumulative potential of components of the mixture: change in the listing (table)	yes
12.3	Bioaccumulative potential: Data are not available.	Bioaccumulative potential: The substance fulfills the very bioaccumulative criterion.	yes
12.6	Other adverse effects: Data are not available.	Other adverse effects	yes
12.6		Endocrine disrupting potential: The mixture contains substance(s) with an endocrine disrupting potential.	yes
13.1	Waste treatment of containers/packages: Completely emptied packages can be recycled. Handle contaminated packages in the same way as the substance itself.	Waste treatment of containers/packages: Only packagings which are approved (e.g. acc. to DOT) may be used. Completely emptied packages can be recycled. Handle contaminated packages in the same way as the substance itself.	yes
14.1	UN number: (not subject to transport regulations)	UN number: 3082	yes
14.2	UN proper shipping name: not relevant	UN proper shipping name: Environmentally hazardous substance, liquid, n.o.s.	yes
14.3	Class: -	Class: 9 (environmentally hazardous)	yes
14.4	Packing group: not relevant	Packing group: III (substance presenting low danger)	yes
14.5	Environmental hazards: none (non-environmentally hazardous acc. to the dangerous goods regulations)	Environmental hazards: hazardous to the aquatic environment	yes
14.7		Information for each of the UN Model Regulations	yes
14.7		Transport of dangerous goods by road or rail (49 CFR US DOT): Not regulated under DOT until packaged in single containers larger than 119 gallons each - liquid, or 882 lbs each - solid.	yes
14.7		Index number: 3082	yes
14.7		Proper shipping name: Environmentally hazardous substance, liquid, n.o.s.	yes
14.7		Particulars in the shipper's declaration: UN3082, Environmentally hazardous substance, liquid, n.o.s., 9, III	yes
14.7		Reportable quantity (RQ): 121,828,571 lbs (55,310,171 kg) (amyl acetate) (4-methylpentan-2-one)	yes
14.7		Class: 9	yes
14.7		Packing group: III	yes



Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

Better Wax VOC

Version number: GHS 10.0
Replaces version of: 2018-10-02 (GHS 9)

Revision: 2019-06-13

Section	Former entry (text/value)	Actual entry (text/value)	Safety-relevant
14.7		Danger label(s): 9, fish and tree	yes
14.7		Danger label(s): change in the listing (table)	yes
14.7		Environmental hazards: yes (hazardous to the aquatic environment)	yes
14.7		Special provisions (SP): 8, 146, 173, 335, IB3, T4, TP1, TP29	yes
14.7		ERG No: 171	yes
14.7		International Maritime Dangerous Goods Code (IM-DG)	yes
14.7		UN number: 3082	yes
14.7		Proper shipping name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.	yes
14.7		Class: 9	yes
14.7		Marine pollutant: yes (hazardous to the aquatic environment)	yes
14.7		Packing group: III	yes
14.7		Danger label(s): 9, fish and tree	yes
14.7		Danger label(s): change in the listing (table)	yes
14.7		Special provisions (SP): 274, 335, 969	yes
14.7		Excepted quantities (EQ): E1	yes
14.7		Limited quantities (LQ): 5 L	yes
14.7		EmS: F-A, S-F	yes
14.7		Stowage category: A	yes
14.7		International Civil Aviation Organization (ICAO-IATA/DGR)	yes
14.7		UN number: 3082	yes
14.7		Proper shipping name: Environmentally hazardous substance, liquid, n.o.s.	yes
14.7		Class: 9	yes
14.7		Environmental hazards: yes (hazardous to the aquatic environment)	yes



Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

Better Wax VOC

Version number: GHS 10.0
Replaces version of: 2018-10-02 (GHS 9)

Revision: 2019-06-13

Section	Former entry (text/value)	Actual entry (text/value)	Safety-relevant
14.7		Packing group: III	yes
14.7		Danger label(s): 9, fish and tree	yes
14.7		Danger label(s): change in the listing (table)	yes
14.7		Special provisions (SP): A97, A158, A197	yes
14.7		Excepted quantities (EQ): E1	yes
14.7		Limited quantities (LQ): 30 kg	yes
15.1	National regulations (United States)		yes
15.1	Toxic Substance Control Act (TSCA): all ingredients are listed or exempt from listing		yes
15.1	Superfund Amendment and Reauthorization Act (SARA TITLE III)		yes
15.1	The List of Extremely Hazardous Substances and Their Threshold Planning Quantities (EPCRA Sec- tion 302, 304): none of the ingredients are listed		yes
15.1	Industry or sector specific available guidance(s)		yes
15.1	NPCA-HMIS® III: Hazardous Materials Identification System (Americ- an Coatings Association)		yes
15.1		NPCA-HMIS® III: change in the listing (table)	yes
15.1	NFPA® 704: National Fire Protection Association: Standard Sys- tem for the Identification of the Hazards of Materials for Emergency Response (United States)		yes
15.1		NFPA® 704: change in the listing (table)	yes
15.1	Right to Know Hazardous Substance List		yes
15.1		Right to Know Hazardous Substance List: change in the listing (table)	yes
15.1	Proposition 65 List of chemicals		yes
15.1		Proposition 65 List of chemicals: change in the listing (table)	yes
15.1	Relevant European Union (EU) safety, health and environmental provisions		yes
15.1	Classification according to GHS (1272/2008/EC, CLP)		yes
15.1		Classification according to GHS (1272/2008/EC, CLP): change in the listing (table)	yes
15.1		National regulations (United States)	yes



Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

Better Wax VOC

Version number: GHS 10.0
Replaces version of: 2018-10-02 (GHS 9)

Revision: 2019-06-13

Section	Former entry (text/value)	Actual entry (text/value)	Safety-relevant
15.1.50.1		Toxic Substance Control Act (TSCA): all ingredients are listed	yes
15.1.50.1		Superfund Amendment and Reauthorization Act (SARA TITLE III)	yes
15.1.50.1		The List of Extremely Hazardous Substances and Their Threshold Planning Quantities (EPCRA Sec- tion 302, 304): none of the ingredients are listed	yes
15.1.50.1		Clean Air Act: none of the ingredients are listed	yes
15.1.50.5		New Jersey Worker and Community Right to Know Act	yes
15.1.50.5		Right to Know Hazardous Substance List: change in the listing (table)	yes
15.1.50.6		California Environmental Protection Agency (Cal/ EPA): Proposition 65 - Safe Drinking Water and Toxic Enforcement Act of 1987	yes
15.1.50.6		Proposition 65 List of chemicals: change in the listing (table)	yes
15.1.50.6		Industry or sector specific available guidance(s)	yes
15.1.50.6		NPCA-HMIS® III: Hazardous Materials Identification System. Americ- an Coatings Association.	yes
15.1.50.6		NPCA-HMIS® III: change in the listing (table)	yes
15.1.50.6		NFPA® 704: National Fire Protection Association: Standard Sys- tem for the Identification of the Hazards of Materials for Emergency Response (United States).	yes
15.1.50.6		NFPA® 704: change in the listing (table)	yes
15.1.50.6		National inventories	yes
15.1.50.6		National inventories: change in the listing (table)	yes
15.2		Chemical Safety Assessment: Chemical safety assessments for substances in this mixture were not carried out.	yes
16	Key literature references and sources for data: - OSHA Hazard Communication Standard (HCS), 29 CFR 1910.1200 - 49 CFR § 172.101 Hazardous Materials Table (DOT)	Key literature references and sources for data: OSHA Hazard Communication Standard (HCS), 29 CFR 1910.1200. Transport of dangerous goods by road or rail (49 CFR US DOT). International Mari- time Dangerous Goods Code (IMDG). Dangerous Goods Regulations (DGR) for the air transport (IATA).	yes
16		List of relevant phrases (code and full text as stated in chapter 2 and 3): change in the listing (table)	yes



Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

Better Wax VOC

Version number: GHS 10.0
Replaces version of: 2018-10-02 (GHS 9)

Revision: 2019-06-13

Abbreviations and acronyms

Abbr.	Descriptions of used abbreviations
29 CFR 1910.1000	29 CFR 1910.1000, Tables Z-1, Z-2, Z-3 - Occupational Safety and Health Standards: Toxic and Hazardous Substances (permissible exposure limits)
49 CFR US DOT	49 CFR § 40 U.S. Department of Transportation
Acute Tox.	Acute toxicity
Asp. Tox.	Aspiration hazard
ATE	Acute Toxicity Estimate
Carc.	Carcinogenicity
CAS	Chemical Abstracts Service (service that maintains the most comprehensive list of chemical substances)
Ceiling-C	Ceiling value
DGR	Dangerous Goods Regulations (see IATA/DGR)
DNEL	Derived No-Effect Level
DOT	Department of Transportation (USA)
EmS	Emergency Schedule
ERG No	Emergency Response Guidebook - Number
Eye Dam.	Seriously damaging to the eye
Eye Irrit.	Irritant to the eye
Flam. Liq.	Flammable liquid
GHS	"Globally Harmonized System of Classification and Labelling of Chemicals" developed by the United Nations
IARC	International Agency for Research on Cancer
IATA	International Air Transport Association
IATA/DGR	Dangerous Goods Regulations (DGR) for the air transport (IATA)
ICAO	International Civil Aviation Organization
IMDG	International Maritime Dangerous Goods Code
MARPOL	International Convention for the Prevention of Pollution from Ships (abbr. of "Marine Pollutant")
NPCA-HMIS® III	National Paint and Coatings Association: Hazardous Materials Identification System - HMIS® III, Third Edition
OSHA	Occupational Safety and Health Administration (United States)
PBT	Persistent, Bioaccumulative and Toxic
PEL	Permissible exposure limit
PNEC	Predicted No-Effect Concentration
ppm	Parts per million
Repr.	Reproductive toxicity
Skin Corr.	Corrosive to skin
Skin Irrit.	Irritant to skin
STEL	Short-term exposure limit
STOT SE	Specific target organ toxicity - single exposure
TWA	Time-weighted average



Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

Better Wax VOC

Version number: GHS 10.0
Replaces version of: 2018-10-02 (GHS 9)

Revision: 2019-06-13

Abbr.	Descriptions of used abbreviations
vPvB	Very Persistent and very Bioaccumulative

Key literature references and sources for data

OSHA Hazard Communication Standard (HCS), 29 CFR 1910.1200.

Transport of dangerous goods by road or rail (49 CFR US DOT). International Maritime Dangerous Goods Code (IMDG). Dangerous Goods Regulations (DGR) for the air transport (IATA).

Classification procedure

Physical and chemical properties: The classification is based on tested mixture.

Health hazards, Environmental hazards: The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

List of relevant phrases (code and full text as stated in chapter 2 and 3)

Code	Text
H225	Highly flammable liquid and vapor.
H226	Flammable liquid and vapor.
H227	Combustible liquid.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H336	May cause drowsiness or dizziness.
H350	May cause cancer.
H361f	Suspected of damaging fertility.

Disclaimer

This information is based upon the present state of our knowledge. This SDS has been compiled and is solely intended for this product.