

acc. to 29 CFR 1910.1200 App D

## **Black Magic**

Version number: GHS 2.0 Revision: 2019-06-14 Replaces version of: 2019-03-27 (GHS 1)

#### **SECTION 1: Identification**

#### 1.1 Product identifier

Trade name Black Magic

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses Vehicle polish

#### 1.3 Details of the supplier of the safety data sheet

B&B Blending, LLC 10963 Leroy Drive Northglenn CO 80233 United States

Telephone: 1.800.875.6320, 1.303.289.6320

e-mail: info@bbblending.com Website: bbblending.com

e-mail (competent person) btirrell@bbblending.com

#### 1.4 Emergency telephone number

Emergency information service USA 1.800.535.5053, INTL 1.352.323.3500

24 hr emergency information

#### SECTION 2: Hazard(s) identification

#### 2.1 Classification of the substance or mixture

Classification acc. to OSHA "Hazard Communication Standard" (29 CFR 1910.1200)

Section	Hazard class	Category	Hazard class and category	Hazard state- ment
A.2	skin corrosion/irritation	2	Skin Irrit. 2	H315
A.7	reproductive toxicity	2	Repr. 2	H361f
B.6	flammable liquid	4	Flam. Liq. 4	H227

For full text of abbreviations: see SECTION 16.

The most important adverse physicochemical, human health and environmental effects

The product is combustible and can be ignited by potential ignition sources. The mixture contains a substance that was identified as a PBT (persistent, bioaccumulative and toxic). The mixture contains a substance that was identified as vPvB (very persistent and very bioaccumulative).

#### Additional information

Containing a PBT-/vPvB-substance in a concentration of  $\geq 0.1\%$ .

#### 2.2 Label elements

Labelling acc. to OSHA "Hazard Communication Standard" (29 CFR 1910.1200)

- Signal word warning

- Pictograms

GHS07, GHS08



United States: en Page: 1 / 15



acc. to 29 CFR 1910.1200 App D

## **Black Magic**

Version number: GHS 2.0
Revision: 2019-06-14
Replaces version of: 2019-03-27 (GHS 1)

- Hazard statements

H227 Combustible liquid. H315 Causes skin irritation.

H361f Suspected of damaging fertility.

- Precautionary statements

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read and understood.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P281 Wear personal protective equipment/face protection.

P302+P352 If on skin: Wash with plenty of water.

P308+P313 If exposed or concerned: Get medical advice/attention.

P321 Specific treatment (see on this label).

P332+P313 If skin irritation occurs: Get medical advice/attention.
P362 Take off contaminated clothing and wash it before reuse.

P370+P378 In case of fire: Use sand, carbon dioxide or powder extinguisher to extinguish.

P403+P235 Store in a well-ventilated place. Keep cool.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

- Hazardous ingredients for labelling

octamethylcyclotetrasiloxane

#### 2.3 Other hazards

This material is combustible, but will not ignite readily. Special danger of slipping by leaking/spilling product.

Hazards not otherwise classified

Very toxic to aquatic life with long lasting effects (GHS category 1: aquatic toxicity - acute and/or chronic).

#### **SECTION 3: Composition/information on ingredients**

#### 3.1 Substances

Not relevant (mixture)

#### 3.2 Mixtures

Description of the mixture

Hazardous	ingredients	acc.	to	<b>GHS</b>
-----------	-------------	------	----	------------

Name of substance	Identifier	Wt%	Classification acc. to GHS	Notes
odorless mineral spirits	CAS No 64742-48-9	12-<20	Skin Irrit. 2 / H315 STOT SE 3 / H336 Asp. Tox. 1 / H304 Flam. Liq. 3 / H226	
China Clay, calcined	CAS No 66402-68-4	3-<12	Acute Tox. 4 / H332	
octamethylcyclotetrasiloxane	CAS No 556-67-2	1-<3	Repr. 2 / H361f Flam. Liq. 3 / H226	PBT vPvB
decamethylcyclopentasilox- ane	CAS No 541-02-6	0.1 - < 1	Flam. Liq. 4 / H227	PBT vPvB

Notes

PBT: The substance was identified as a PBT (persistent, bioaccumulative and toxic) vPvB: The substance was identified as a vPvB (very persistent and very bioaccumulative)

United States: en Page: 2 / 15



acc. to 29 CFR 1910.1200 App D

## **Black Magic**

Version number: GHS 2.0 Revision: 2019-06-14 Replaces version of: 2019-03-27 (GHS 1)

For full text of abbreviations: see SECTION 16. Exact percentage of ingredients is withheld as a trade secret.

#### **SECTION 4: First-aid measures**

#### 4.1 Description of first- aid measures

#### General notes

Do not leave affected person unattended. Remove victim out of the danger area. Keep affected person warm, still and covered. Take off immediately all contaminated clothing. In all cases of doubt, or when symptoms persist, seek medical advice. In case of unconsciousness place person in the recovery position. Never give anything by mouth.

#### Following inhalation

If breathing is irregular or stopped, immediately seek medical assistance and start first aid actions. In case of respiratory tract irritation, consult a physician. Provide fresh air.

#### Following skin contact

Wash with plenty of soap and water.

#### Following eye contact

Remove contact lenses, if present and easy to do. Continue rinsing.

#### Following ingestion

Rinse mouth with water (only if the person is conscious). Do NOT induce vomiting.

#### **SECTION 5: Fire-fighting measures**

#### 5.1 Extinguishing media

Suitable extinguishing media

Water spray, BC-powder, Carbon dioxide (CO2)

Unsuitable extinguishing media

Water jet

#### 5.2 Special hazards arising from the substance or mixture

In case of insufficient ventilation and/or in use, may form flammable/explosive vapor-air mixture. Solvent vapors are heavier than air and may spread along floors. Places which are not ventilated, e.g. unventilated below ground level areas such as trenches, conduits and shafts, are particularly prone to the presence of flammable substances or mixtures.

#### Hazardous combustion products

Nitrogen oxides (NOx), Carbon monoxide (CO), Carbon dioxide (CO2)

#### 5.3 Advice for firefighters

In case of fire and/or explosion do not breathe fumes. Co-ordinate firefighting measures to the fire surroundings. Do not allow firefighting water to enter drains or water courses. Collect contaminated firefighting water separately. Fight fire with normal precautions from a reasonable distance.

#### **SECTION 6: Accidental release measures**

#### 6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

Remove persons to safety.

#### For emergency responders

Wear breathing apparatus if exposed to vapors/dust/aerosols/gases.

United States: en Page: 3 / 15



acc. to 29 CFR 1910.1200 App D

## **Black Magic**

Version number: GHS 2.0 Revision: 2019-06-14 Replaces version of: 2019-03-27 (GHS 1)

#### 6.2 Environmental precautions

Keep away from drains, surface and ground water. Retain contaminated washing water and dispose of it. If substance has entered a water course or sewer, inform the responsible authority.

#### 6.3 Methods and material for containment and cleaning up

Advices on how to contain a spill

Covering of drains

Advices on how to clean up a spill

Wipe up with absorbent material (e.g. cloth, fleece). Collect spillage: sawdust, kieselgur (diatomite), sand, universal binder

Appropriate containment techniques

Use of adsorbent materials.

Other information relating to spills and releases

Place in appropriate containers for disposal. Ventilate affected area.

#### 6.4 Reference to other sections

Hazardous combustion products: see section 5. Personal protective equipment: see section 8. Incompatible materials: see section 10. Disposal considerations: see section 13.

#### **SECTION 7: Handling and storage**

#### 7.1 Precautions for safe handling

Recommendations

- Measures to prevent fire as well as aerosol and dust generation

Use local and general ventilation. Avoidance of ignition sources. Keep away from sources of ignition - No smoking. Take precautionary measures against static discharge. Use only in well-ventilated areas. Due to danger of explosion, prevent leakage of vapours into cellars, flues and ditches. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting/equipment. Use only non-sparking tools.

- Specific notes/details

Places which are not ventilated, e.g. unventilated below ground level areas such as trenches, conduits and shafts, are particularly prone to the presence of flammable substances or mixtures. Vapors are heavier than air, spread along floors and form explosive mixtures with air. Vapors may form explosive mixtures with air.

#### Advice on general occupational hygiene

Wash hands after use. Do not eat, drink and smoke in work areas. Remove contaminated clothing and protective equipment before entering eating areas. Never keep food or drink in the vicinity of chemicals. Never place chemicals in containers that are normally used for food or drink. Keep away from food, drink and animal feedingstuffs.

#### 7.2 Conditions for safe storage, including any incompatibilities

Managing of associated risks

- Explosive atmospheres

Keep container tightly closed and in a well-ventilated place. Use local and general ventilation. Keep cool. Protect from sunlight.

- Flammability hazards

Keep away from sources of ignition - No smoking. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Take precautionary measures against static discharge. Protect from sunlight.

Control of the effects

Protect against external exposure, such as

Frost

- Ventilation requirements

Use local and general ventilation. Ground/bond container and receiving equipment.

United States: en Page: 4 / 15



acc. to 29 CFR 1910.1200 App D

## **Black Magic**

Version number: GHS 2.0 Revision: 2019-06-14 Replaces version of: 2019-03-27 (GHS 1)

- Packaging compatibilities

Only packagings which are approved (e.g. acc. to the Dangerous Goods Regulations) may be used.

#### 7.3 Specific end use(s)

See section 16 for a general overview.

#### SECTION 8: Exposure controls/personal protection

#### 8.1 Control parameters

Occupational exposure limit values (Workplace Exposure Limits)

Coun try	Name of agent	CAS No	Iden- tifier	TWA [ppm]	TWA [mg/ m³]	STEL [ppm]	STEL [mg/ m³]	Ceil- ing-C [ppm]	Ceil- ing-C [mg/ m³]	Nota tion	Sourc e
US	petroleum distil- lates (naphtha) (rubber solvent)	64742- 48-9	PEL	500	2,000						29 CFR 1910.1 000

Notation

Ceiling-C STEL

ceiling value is a limit value above which exposure should not occur

STEL short-term exposure limit: a limit value above which exposure should not occur and which is related to a 15-minute period (unless otherwise specified)

otherwise specified)
TWA time-weighted avera

time-weighted average (long-term exposure limit): measured or calculated in relation to a reference period of 8 hours time-weighted average (unless otherwise specified

#### Relevant DNELs of components of the mixture

Name of substance	CAS No	End- point	Threshold level	Protection goal, route of exposure	Used in	Exposure time
China Clay, calcined	66402-68-4	DNEL	15.63 mg/m <sup>3</sup>	human, inhalatory	worker (industry)	chronic - local ef- fects
octamethylcyclotet- rasiloxane	556-67-2	DNEL	73 mg/m <sup>3</sup>	human, inhalatory	worker (industry)	chronic - systemic effects
octamethylcyclotet- rasiloxane	556-67-2	DNEL	73 mg/m <sup>3</sup>	human, inhalatory	worker (industry)	acute - systemic effects
octamethylcyclotet- rasiloxane	556-67-2	DNEL	73 mg/m <sup>3</sup>	human, inhalatory	worker (industry)	chronic - local ef- fects
octamethylcyclotet- rasiloxane	556-67-2	DNEL	73 mg/m <sup>3</sup>	human, inhalatory	worker (industry)	acute - local ef- fects
decamethylcyclo- pentasiloxane	541-02-6	DNEL	97.3 mg/m <sup>3</sup>	human, inhalatory	worker (industry)	chronic - systemic effects
decamethylcyclo- pentasiloxane	541-02-6	DNEL	97.3 mg/m <sup>3</sup>	human, inhalatory	worker (industry)	acute - systemic effects
decamethylcyclo- pentasiloxane	541-02-6	DNEL	24.2 mg/m <sup>3</sup>	human, inhalatory	worker (industry)	chronic - local ef- fects
decamethylcyclo- pentasiloxane	541-02-6	DNEL	24.2 mg/m <sup>3</sup>	human, inhalatory	worker (industry)	acute - local ef- fects

United States: en Page: 5 / 15





acc. to 29 CFR 1910.1200 App D

## **Black Magic**

Version number: GHS 2.0 Replaces version of: 2019-03-27 (GHS 1)

Revision: 2019-06-14

### Relevant PNECs of components of the mixture

Name of substance	CAS No	End- point	Threshold level	Organism	Environmental compartment	Exposure time
octamethylcyclotet- rasiloxane	556-67-2	PNEC	10 <sup>mg</sup> / <sub>l</sub>	microorganisms	sewage treatment plant (STP)	short-term (single instance)
octamethylcyclotet- rasiloxane	556-67-2	PNEC	0.059 <sup>mg</sup> / <sub>kg</sub>	pelagic organisms	sediment	short-term (single instance)
octamethylcyclotet- rasiloxane	556-67-2	PNEC	1.7 <sup>mg</sup> / <sub>kg</sub>	(top) predators	water	short-term (single instance)
octamethylcyclotet- rasiloxane	556-67-2	PNEC	0.44 <sup>µg</sup> / <sub>l</sub>	aquatic organisms	freshwater	short-term (single instance)
octamethylcyclotet- rasiloxane	556-67-2	PNEC	0.044 <sup>µg</sup> / <sub>I</sub>	aquatic organisms	marine water	short-term (single instance)
octamethylcyclotet- rasiloxane	556-67-2	PNEC	10 <sup>mg</sup> / <sub>l</sub>	aquatic organisms	sewage treatment plant (STP)	short-term (single instance)
octamethylcyclotet- rasiloxane	556-67-2	PNEC	3 <sup>mg</sup> / <sub>kg</sub>	aquatic organisms	freshwater sedi- ment	short-term (single instance)
octamethylcyclotet- rasiloxane	556-67-2	PNEC	0.3 <sup>mg</sup> / <sub>kg</sub>	aquatic organisms	marine sediment	short-term (single instance)
octamethylcyclotet- rasiloxane	556-67-2	PNEC	0.59 <sup>mg</sup> / <sub>kg</sub>	benthic organisms	sediment	short-term (single instance)
octamethylcyclotet- rasiloxane	556-67-2	PNEC	0.16 <sup>mg</sup> / <sub>kg</sub>	terrestrial organisms	soil	short-term (single instance)
decamethylcyclo- pentasiloxane	541-02-6	PNEC	10 <sup>mg</sup> / <sub>l</sub>	microorganisms	sewage treatment plant (STP)	short-term (single instance)
decamethylcyclo- pentasiloxane	541-02-6	PNEC	11 <sup>mg</sup> / <sub>kg</sub>	benthic organisms	sediment	short-term (single instance)
decamethylcyclo- pentasiloxane	541-02-6	PNEC	13 <sup>mg</sup> / <sub>kg</sub>	(top) predators	water	short-term (single instance)
decamethylcyclo- pentasiloxane	541-02-6	PNEC	1.1 <sup>mg</sup> / <sub>kg</sub>	pelagic organisms	sediment	short-term (single instance)
decamethylcyclo- pentasiloxane	541-02-6	PNEC	1.2 <sup>µg</sup> / <sub>l</sub>	aquatic organisms	freshwater	short-term (single instance)
decamethylcyclo- pentasiloxane	541-02-6	PNEC	0.12 <sup>µg</sup> / <sub>l</sub>	aquatic organisms	marine water	short-term (single instance)
decamethylcyclo- pentasiloxane	541-02-6	PNEC	10 <sup>mg</sup> / <sub>l</sub>	aquatic organisms	sewage treatment plant (STP)	short-term (single instance)
decamethylcyclo- pentasiloxane	541-02-6	PNEC	11 <sup>mg</sup> / <sub>kg</sub>	aquatic organisms	freshwater sedi- ment	short-term (single instance)
decamethylcyclo- pentasiloxane	541-02-6	PNEC	1.1 <sup>mg</sup> / <sub>kg</sub>	aquatic organisms	marine sediment	short-term (single instance)
decamethylcyclo- pentasiloxane	541-02-6	PNEC	1.27 <sup>mg</sup> / <sub>kg</sub>	terrestrial organisms	soil	short-term (single instance)

### 8.2 Exposure controls

Appropriate engineering controls General ventilation.

United States: en Page: 6 / 15



acc. to 29 CFR 1910.1200 App D

## **Black Magic**

Version number: GHS 2.0 Replaces version of: 2019-03-27 (GHS 1)

Individual protection measures (personal protective equipment)

#### Eye/face protection

Wear eye/face protection.

#### Skin protection

#### - Hand protection

Wear suitable gloves. Chemical protection gloves are suitable, which are tested according to EN 374. Check leak-tightness/impermeability prior to use. In the case of wanting to use the gloves again, clean them before taking off and air them well. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

Revision: 2019-06-14

#### - Other protection measures

Take recovery periods for skin regeneration. Preventive skin protection (barrier creams/ointments) is recommended. Wash hands thoroughly after handling.

#### Respiratory protection

In case of inadequate ventilation wear respiratory protection.

#### Environmental exposure controls

Use appropriate container to avoid environmental contamination. Keep away from drains, surface and ground water.

#### **SECTION 9: Physical and chemical properties**

#### 9.1 Information on basic physical and chemical properties

#### **Appearance**

Physical state	liquid (viscous)
Color	white
Odor	sweet

#### Other safety parameters

pH (value)	not determined
Melting point/freezing point	not determined
Initial boiling point and boiling range	>65 °C at 1 atm
Flash point	63 °C at 101.3 kPa 146 °F at 1 atm
Evaporation rate	not determined
Flammability (solid, gas)	not relevant, (fluid)

#### **Explosive limits**

- Lower explosion limit (LEL)	0.7 vol%
- Upper explosion limit (UEL)	5.4 vol%

United States: en Page: 7 / 15



acc. to 29 CFR 1910.1200 App D

## **Black Magic**

Version number: GHS 2.0 Replaces version of: 2019-03-27 (GHS 1)

Vapor pressure	31.69 hPa at 25 °C
Density	1.008 <sup>g</sup> / <sub>ml</sub>
Vapor density	this information is not available
Relative density	1 (water = 1)
Solubility(ies)	not determined

Revision: 2019-06-14

#### Partition coefficient

- n-octanol/water (log KOW)	this information is not available
Auto-ignition temperature	343 °C

#### Viscosity

- Kinematic viscosity	50,000 cSt at 25 °C
- Dynamic viscosity	50,401 cP
Explosive properties	none
Oxidizing properties	none

#### 9.2 Other information

Temperature class (USA, acc. to NEC 500)	T2 (maximum permissible surface temperature on the equipment:
	300°C)

## **SECTION 10: Stability and reactivity**

#### 10.1 Reactivity

Concerning incompatibility: see below "Conditions to avoid" and "Incompatible materials". The mixture contains reactive substance(s). Risk of ignition.

If heated:

Risk of ignition

#### 10.2 Chemical stability

See below "Conditions to avoid".

#### 10.3 Possibility of hazardous reactions

No known hazardous reactions.

#### 10.4 Conditions to avoid

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

#### Hints to prevent fire or explosion

Use explosion-proof electrical/ventilating/lighting/equipment. Use only non-sparking tools. Take precautionary measures against static discharge.

#### 10.5 Incompatible materials

Oxidizers

United States: en Page: 8 / 15



acc. to 29 CFR 1910.1200 App D

## **Black Magic**

Version number: GHS 2.0 Replaces version of: 2019-03-27 (GHS 1)

#### replaces version of: 2019-03-27 (GHS 1)

#### 10.6 Hazardous decomposition products

Reasonably anticipated hazardous decomposition products produced as a result of use, storage, spill and heating are not known. Hazardous combustion products: see section 5.

Revision: 2019-06-14

#### **SECTION 11: Toxicological information**

#### 11.1 Information on toxicological effects

Test data are not available for the complete mixture.

Classification procedure

The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

#### Classification acc. to OSHA "Hazard Communication Standard" (29 CFR 1910.1200)

Acute toxicity

Shall not be classified as acutely toxic.

#### Acute toxicity estimate (ATE) of components of the mixture

Name of substance	CAS No	Exposure route	ATE
China Clay, calcined	66402-68-4	inhalation: dust/mist	2.3 <sup>mg</sup> / <sub>l</sub> /4h

#### Skin corrosion/irritation

Causes skin irritation.

#### Serious eye damage/eye irritation

Shall not be classified as seriously damaging to the eye or eye irritant.

#### Respiratory or skin sensitization

Shall not be classified as a respiratory or skin sensitizer.

#### Germ cell mutagenicity

Shall not be classified as germ cell mutagenic.

#### Carcinogenicity

Shall not be classified as carcinogenic.

#### Reproductive toxicity

Suspected of damaging fertility.

#### Specific target organ toxicity - single exposure

Shall not be classified as a specific target organ toxicant (single exposure).

#### Specific target organ toxicity - repeated exposure

Shall not be classified as a specific target organ toxicant (repeated exposure).

#### Aspiration hazard

Shall not be classified as presenting an aspiration hazard.

United States: en Page: 9 / 15





acc. to 29 CFR 1910.1200 App D

## **Black Magic**

Version number: GHS 2.0 Revision: 2019-06-14 Replaces version of: 2019-03-27 (GHS 1)

#### **SECTION 12: Ecological information**

#### 12.1 Toxicity

Very toxic to aquatic life with long lasting effects.

### Aquatic toxicity (acute) of components of the mixture

Name of substance	CAS No	Endpoint	Value	Species	Exposure time
octamethylcyclotet- rasiloxane	556-67-2	LC50	>22 <sup>µg</sup> / <sub>I</sub>	fish	96 h
octamethylcyclotet- rasiloxane	556-67-2	EC50	>1,000 <sup>mg</sup> / <sub>I</sub>	aquatic invertebrates	96 h
decamethylcyclopentas- iloxane	541-02-6	LC50	>16 <sup>µg</sup> / <sub>I</sub>	fish	96 h
decamethylcyclopentas- iloxane	541-02-6	EC50	>2.9 <sup>µg</sup> / <sub>I</sub>	aquatic invertebrates	48 h

#### Aquatic toxicity (chronic) of components of the mixture

Name of substance	CAS No	Endpoint	Value	Species	Exposure time
odorless mineral spirits	64742-48-9	EC50	15.41 <sup>mg</sup> / <sub>l</sub>	microorganisms	40 h
China Clay, calcined	66402-68-4	EC50	300.4 <sup>mg</sup> / <sub>l</sub>	microorganisms	3 h
octamethylcyclotet- rasiloxane	556-67-2	LC50	10 <sup>µg</sup> / <sub>I</sub>	fish	14 d
octamethylcyclotet- rasiloxane	556-67-2	EC50	>500 <sup>mg</sup> / <sub>I</sub>	aquatic invertebrates	24 h
decamethylcyclopentas- iloxane	541-02-6	LC50	>16 <sup>µg</sup> / <sub>I</sub>	fish	14 d
decamethylcyclopentas- iloxane	541-02-6	EC50	>15 <sup>µg</sup> / <sub>I</sub>	aquatic invertebrates	21 d

#### 12.2 Persistence and degradability

Data are not available.

#### 12.3 Bioaccumulative potential

The substance fulfills the very bioaccumulative criterion.

#### 12.4 Mobility in soil

Data are not available.

#### 12.5 Results of PBT and vPvB assessment

The mixture contains a substance that was identified as a PBT (persistent, bioaccumulative and toxic). The mixture contains a substance that was identified as vPvB (very persistent and very bioaccumulative).

United States: en Page: 10 / 15



acc. to 29 CFR 1910.1200 App D

## **Black Magic**

Version number: GHS 2.0
Revision: 2019-06-14
Replaces version of: 2019-03-27 (GHS 1)

#### 12.6 Other adverse effects

Endocrine disrupting potential

The mixture contains substance(s) with an endocrine disrupting potential.

#### **SECTION 13: Disposal considerations**

#### 13.1 Waste treatment methods

Waste treatment-relevant information

Solvent reclamation/regeneration.

Sewage disposal-relevant information

Do not empty into drains. Avoid release to the environment. Refer to special instructions/safety data sheets.

Waste treatment of containers/packages

Only packagings which are approved (e.g. acc. to DOT) may be used. Completely emptied packages can be recycled. Handle contaminated packages in the same way as the substance itself.

#### Remarks

Please consider the relevant national or regional provisions. Waste shall be separated into the categories that can be handled separately by the local or national waste management facilities.

#### **SECTION 14: Transport information**

**14.1 UN number** 3082

**14.2 UN proper shipping name** Environmentally hazardous substance, liquid, n.o.s.

14.3 Transport hazard class(es)

Class 9 (environmentally hazardous)

14.4 Packing group III (substance presenting low danger)

**14.5 Environmental hazards** hazardous to the aquatic environment

14.6 Special precautions for user

There is no additional information.

#### 14.7 Transport in bulk according to Annex II of MARPOL and the IBC Code

The cargo is not intended to be carried in bulk.

#### Information for each of the UN Model Regulations

#### Transport of dangerous goods by road or rail (49 CFR US DOT)

Not regulated under DOT until packaged in single containers larger than 119 gallons each - liquid, or 882 lbs each - solid.

Index number 3082

Proper shipping name Environmentally hazardous substance, liquid, n.o.s.

- Particulars in the shipper's declaration UN3082, Environmentally hazardous substance, li-

quid, n.o.s., 9, III

Class 9
Packing group III

Danger label(s) 9, fish and tree



United States: en Page: 11 / 15

# R

## Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

## **Black Magic**

Version number: GHS 2.0
Revision: 2019-06-14
Replaces version of: 2019-03-27 (GHS 1)

Environmental hazards yes (hazardous to the aquatic environment)
Special provisions (SP)
8, 146, 173, 335, IB3, T4, TP1, TP29

ERG No 171

**International Maritime Dangerous Goods Code (IMDG)** 

Proper shipping name ENVIRONMENTALLY HAZARDOUS SUBSTANCE,

3082

LIQUID, N.O.S.

Class 9

Marine pollutant yes (hazardous to the aquatic environment)

Packing group II

Danger label(s) 9, fish and tree

**UN** number

Special provisions (SP) 274, 335, 969

Excepted quantities (EQ) E1
Limited quantities (LQ) 5 L
EmS F-A, S-F

Stowage category A

International Civil Aviation Organization (ICAO-IATA/DGR)

UN number 3082

Proper shipping name Environmentally hazardous substance, liquid, n.o.s.

Class 9

Environmental hazards yes (hazardous to the aquatic environment)

Packing group II

Danger label(s) 9, fish and tree

Special provisions (SP) A97, A158, A197

Excepted quantities (EQ) E1
Limited quantities (LQ) 30 kg

#### **SECTION 15: Regulatory information**

# 15.1 Safety, health and environmental regulations specific for the product in question National regulations (United States)

#### Superfund Amendment and Reauthorization Act (SARA TITLE III )

- The List of Extremely Hazardous Substances and Their Threshold Planning Quantities (EPCRA Section 302, 304)

none of the ingredients are listed

United States: en Page: 12 / 15



acc. to 29 CFR 1910.1200 App D

## **Black Magic**

Version number: GHS 2.0
Revision: 2019-06-14
Replaces version of: 2019-03-27 (GHS 1)

#### Comprehensive Environmental Response, Compensation, and Liability Act (CERCLA)

- List of Hazardous Substances and Reportable Quantities (CERCLA section 102a) (40 CFR 302.4) none of the ingredients are listed

#### **Clean Air Act**

none of the ingredients are listed

## 15.1.5 California Environmental Protection Agency (Cal/EPA): Proposition 65 - Safe Drinking Water and 0.6 Toxic Enforcement Act of 1987

Proposition 65 List of chemicals				
Name acc. to inventory	CAS No	Conc.	Remarks	Type of the toxicity
carbon black	1333-86-4	0.036 wt%	airborne, unbound particles of respirable size	cancer

# Industry or sector specific available guidance(s) NPCA-HMIS® III

Hazardous Materials Identification System. American Coatings Association.

Category	Rating	Description
Chronic	*	chronic (long-term) health effects may result from repeated overexposure
Health	2	temporary or minor injury may occur
Flammability	2	material that must be moderately heated or exposed to relatively high ambient temperat- ures before ignition can occur
Physical hazard	0	material that is normally stable, even under fire conditions, and will not react with water, polymerize, decompose, condense, or self-react. Non-explosive
Personal protection	-	

Chronic: chronic hazard
Flammability: flammability hazard
Health: health hazard

Personal protection: personal protective equipment (PPE) for normal use

Physical hazard: reactivity

#### **NFPA® 704**

National Fire Protection Association: Standard System for the Identification of the Hazards of Materials for Emergency Response (United States).

Category	Degree of hazard	Description
Flammability	2	material that must be moderately heated or exposed to relatively high ambient temperat- ures before ignition can occur
Health	2	material that, under emergency conditions, can cause temporary incapacitation or residual injury
Instability	0	material that is normally stable, even under fire conditions
Special hazard		

United States: en Page: 13 / 15



acc. to 29 CFR 1910.1200 App D

## **Black Magic**

Version number: GHS 2.0 Revision: 2019-06-14 Replaces version of: 2019-03-27 (GHS 1)

#### **National inventories**

Country	Inventory	Status
CA	DSL	all ingredients are listed
EU	REACH Reg.	not all ingredients are listed
US	TSCA	all ingredients are listed

Legend

DSL Domestic Substances List (DSL)
REACH Reg. REACH registered substances
TSCA Toxic Substance Control Act

#### 15.2 Chemical Safety Assessment

Chemical safety assessments for substances in this mixture were not carried out.

#### SECTION 16: Other information, including date of preparation or last revision

#### Indication of changes (revised safety data sheet)

Section	Former entry (text/value)	Actual entry (text/value)	Safety- relevant
14.7	Transport of dangerous goods by road or rail (49 CFR US DOT)	Transport of dangerous goods by road or rail (49 CFR US DOT): Not regulated under DOT until packaged in single containers larger than 119 gallons each - liquid, or 882 lbs each - solid.	yes
15.1.50.1	Toxic Substance Control Act (TSCA): all ingredients are listed		yes

#### Abbreviations and acronyms

Abbr.	Descriptions of used abbreviations	
29 CFR 1910.1000	29 CFR 1910.1000, Tables Z-1, Z-2, Z-3 - Occupational Safety and Health Standards: Toxic and Hazardous Substances (permissible exposure limits)	
49 CFR US DOT	49 CFR § 40 U.S. Department of Transportation	
Acute Tox.	Acute toxicity	
Asp. Tox.	Aspiration hazard	
ATE	Acute Toxicity Estimate	
CAS	Chemical Abstracts Service (service that maintains the most comprehensive list of chemical substances)	
Ceiling-C	Ceiling value	
DGR	Dangerous Goods Regulations (see IATA/DGR)	
DNEL	EL Derived No-Effect Level	
DOT	Department of Transportation (USA)	
EmS	Emergency Schedule	
ERG No	Emergency Response Guidebook - Number	
Flam. Liq.	Flammable liquid	
GHS	"Globally Harmonized System of Classification and Labelling of Chemicals" developed by the United Nations	
IATA	International Air Transport Association	

United States: en Page: 14 / 15



acc. to 29 CFR 1910.1200 App D

Revision: 2019-06-14

## **Black Magic**

Version number: GHS 2.0 Replaces version of: 2019-03-27 (GHS 1)

	27 (0.10-1)
Abbr.	Descriptions of used abbreviations
IATA/DGR	Dangerous Goods Regulations (DGR) for the air transport (IATA)
ICAO	International Civil Aviation Organization
IMDG	International Maritime Dangerous Goods Code
MARPOL	International Convention for the Prevention of Pollution from Ships (abbr. of "Marine Pollutant")
NPCA-HMIS® III	National Paint and Coatings Association: Hazardous Materials Identification System - HMIS® III, Third Edition
OSHA	Occupational Safety and Health Administration (United States)
PBT	Persistent, Bioaccumulative and Toxic
PEL	Permissible exposure limit
PNEC	Predicted No-Effect Concentration
ppm	Parts per million
Repr.	Reproductive toxicity
Skin Corr.	Corrosive to skin
Skin Irrit.	Irritant to skin
STEL	Short-term exposure limit
STOT SE	Specific target organ toxicity - single exposure
TWA	Time-weighted average
vPvB	Very Persistent and very Bioaccumulative

#### Key literature references and sources for data

OSHA Hazard Communication Standard (HCS), 29 CFR 1910.1200.

Transport of dangerous goods by road or rail (49 CFR US DOT). International Maritime Dangerous Goods Code (IMDG). Dangerous Goods Regulations (DGR) for the air transport (IATA).

#### Classification procedure

Physical and chemical properties: The classification is based on tested mixture.

Health hazards, Environmental hazards: The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

#### List of relevant phrases (code and full text as stated in chapter 2 and 3)

Code	Text
H226	Flammable liquid and vapor.
H227	Combustible liquid.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H332	Harmful if inhaled.
H336	May cause drowsiness or dizziness.
H361f	Suspected of damaging fertility.

#### **Disclaimer**

This information is based upon the present state of our knowledge. This SDS has been compiled and is solely intended for this product.

United States: en Page: 15 / 15