

Tire & Trim

Version number: GHS 7.0
Replaces version of: 2018-06-21 (GHS 6)

Revision: 2019-06-14

SECTION 1: Identification

1.1 Product identifier

Trade name

**Tire &
Trim**

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses

General use

1.3 Details of the supplier of the safety data sheet

B&B Blending, LLC
10963 Leroy Drive
Northglenn CO 80233
United States

Telephone: 1.800.875.6320, 1.303.289.6320
e-mail: info@bbblending.com
Website: bbblending.com

e-mail (competent person)

btirrell@bbblending.com

1.4 Emergency telephone number

Emergency information service

USA 1.800.535.5053, INTL 1.352.323.3500
24 hr emergency information

SECTION 2: Hazard(s) identification

2.1 Classification of the substance or mixture

Classification acc. to OSHA "Hazard Communication Standard" (29 CFR 1910.1200)

Section	Hazard class	Category	Hazard class and category	Hazard statement
A.2	skin corrosion/irritation	2	Skin Irrit. 2	H315
A.8D	specific target organ toxicity - single exposure (narcotic effects, drowsiness)	3	STOT SE 3	H336
A.10	aspiration hazard	1	Asp. Tox. 1	H304
B.6	flammable liquid	2	Flam. Liq. 2	H225

For full text of abbreviations: see SECTION 16.

The most important adverse physicochemical, human health and environmental effects

The product is combustible and can be ignited by potential ignition sources.

2.2 Label elements

Labelling acc. to OSHA "Hazard Communication Standard" (29 CFR 1910.1200)

- Signal word danger

- Pictograms

GHS02, GHS07,
GHS08





Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

Tire & Trim

Version number: GHS 7.0
Replaces version of: 2018-06-21 (GHS 6)

Revision: 2019-06-14

- Hazard statements

H225	Highly flammable liquid and vapor.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H336	May cause drowsiness or dizziness.

- Precautionary statements

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P240	Ground/bond container and receiving equipment.
P241	Use explosion-proof electrical/ventilating/lighting equipment.
P242	Use only non-sparking tools.
P243	Take precautionary measures against static discharge.
P261	Avoid breathing dust/fume/gas/mist/vapors/spray.
P271	Use only outdoors or in a well-ventilated area.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P301+P310	If swallowed: Immediately call a poison center/doctor.
P302+P352	If on skin: Wash with plenty of water.
P303+P361+P353	If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
P304+P340	If inhaled: Remove person to fresh air and keep comfortable for breathing.
P312	Call a poison center/doctor if you feel unwell.
P321	Specific treatment (see on this label).
P331	Do NOT induce vomiting.
P362	Take off contaminated clothing and wash it before reuse.
P370+P378	In case of fire: Use sand, carbon dioxide or powder extinguisher to extinguish.
P403+P233	Store in a well-ventilated place. Keep container tightly closed.
P403+P235	Store in a well-ventilated place. Keep cool.
P405	Store locked up.
P501	Dispose of contents/container in accordance with local/regional/national/international regulations.

- Hazardous ingredients for labelling heptane, distillates (petroleum) hydrotreated, light

2.3 Other hazards

Hazards not otherwise classified

May be harmful if inhaled (GHS category 5: acutely toxic - inhalation).

Toxic to aquatic life with long lasting effects (GHS category 2: aquatic toxicity - acute and/or chronic).

Results of PBT and vPvB assessment

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

SECTION 3: Composition/information on ingredients

3.1 Substances

Not relevant (mixture)

3.2 Mixtures

Description of the mixture

Hazardous ingredients acc. to GHS				
Name of substance	Identifier	Wt%	Classification acc. to GHS	Notes
heptane	CAS No 142-82-5	40 - < 55	Skin Irrit. 2 / H315 STOT SE 3 / H336 Asp. Tox. 1 / H304 Flam. Liq. 2 / H225	C(a) IOELV

Tire & Trim

Version number: GHS 7.0
Replaces version of: 2018-06-21 (GHS 6)

Revision: 2019-06-14

Hazardous ingredients acc. to GHS				
Name of substance	Identifier	Wt%	Classification acc. to GHS	Notes
distillates (petroleum) hydro-treated, light	CAS No 64742-47-8	12 - < 20	Asp. Tox. 1 / H304 Flam. Liq. 4 / H227	
2-butoxy-1-ethanol	CAS No 111-76-2	3 - < 12	Acute Tox. 4 / H302 Acute Tox. 4 / H312 Acute Tox. 4 / H332 Skin Irrit. 2 / H315 Eye Irrit. 2 / H319 Flam. Liq. 4 / H227	IOELV
Propan-2-ol	CAS No 67-63-0	1 - < 3	Eye Irrit. 2 / H319 STOT SE 3 / H336 Flam. Liq. 2 / H225	

Notes

C(a): Mixture of isomers

IOELV: Substance with a community indicative occupational exposure limit value

For full text of abbreviations: see SECTION 16. Exact percentage of ingredients is withheld as a trade secret.

SECTION 4: First-aid measures

4.1 Description of first-aid measures

General notes

Do not leave affected person unattended. Remove victim out of the danger area. Keep affected person warm, still and covered. Take off immediately all contaminated clothing. In all cases of doubt, or when symptoms persist, seek medical advice. In case of unconsciousness place person in the recovery position. Never give anything by mouth.

Following inhalation

If breathing is irregular or stopped, immediately seek medical assistance and start first aid actions. In case of respiratory tract irritation, consult a physician. Provide fresh air.

Following skin contact

Wash with plenty of soap and water.

Following eye contact

Remove contact lenses, if present and easy to do. Continue rinsing.

Following ingestion

Rinse mouth with water (only if the person is conscious). Do NOT induce vomiting.

SECTION 5: Fire-fighting measures

5.1 Extinguishing media

Suitable extinguishing media

Water spray, BC-powder, Carbon dioxide (CO₂)

Unsuitable extinguishing media

Water jet

5.2 Special hazards arising from the substance or mixture

In case of insufficient ventilation and/or in use, may form flammable/explosive vapor-air mixture. Solvent vapors are heavier than air and may spread along floors. Places which are not ventilated, e.g. unventilated below ground level areas such as trenches, conduits and shafts, are particularly prone to the presence of flammable substances or mixtures.

Tire & Trim

Version number: GHS 7.0
Replaces version of: 2018-06-21 (GHS 6)

Revision: 2019-06-14

Hazardous combustion products
Nitrogen oxides (NO_x), Carbon monoxide (CO), Carbon dioxide (CO₂)

5.3 Advice for firefighters

In case of fire and/or explosion do not breathe fumes. Co-ordinate firefighting measures to the fire surroundings. Do not allow firefighting water to enter drains or water courses. Collect contaminated firefighting water separately. Fight fire with normal precautions from a reasonable distance.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

Remove persons to safety.

For emergency responders

Wear breathing apparatus if exposed to vapors/dust/aerosols/gases.

6.2 Environmental precautions

Keep away from drains, surface and ground water. Retain contaminated washing water and dispose of it. If substance has entered a water course or sewer, inform the responsible authority.

6.3 Methods and material for containment and cleaning up

Advices on how to contain a spill

Covering of drains

Advices on how to clean up a spill

Wipe up with absorbent material (e.g. cloth, fleece). Collect spillage: sawdust, kieselgur (diatomite), sand, universal binder

Appropriate containment techniques

Use of adsorbent materials.

Other information relating to spills and releases

Place in appropriate containers for disposal. Ventilate affected area.

6.4 Reference to other sections

Hazardous combustion products: see section 5. Personal protective equipment: see section 8. Incompatible materials: see section 10. Disposal considerations: see section 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Recommendations

- Measures to prevent fire as well as aerosol and dust generation

Use local and general ventilation. Avoidance of ignition sources. Keep away from sources of ignition - No smoking. Take precautionary measures against static discharge. Use only in well-ventilated areas. Due to danger of explosion, prevent leakage of vapours into cellars, flues and ditches. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting/equipment. Use only non-sparking tools.

- Specific notes/details

Places which are not ventilated, e.g. unventilated below ground level areas such as trenches, conduits and shafts, are particularly prone to the presence of flammable substances or mixtures. Vapors are heavier than air, spread along floors and form explosive mixtures with air. Vapors may form explosive mixtures with air.

Tire & Trim

Version number: GHS 7.0
Replaces version of: 2018-06-21 (GHS 6)

Revision: 2019-06-14

Advice on general occupational hygiene

Wash hands after use. Do not eat, drink and smoke in work areas. Remove contaminated clothing and protective equipment before entering eating areas. Never keep food or drink in the vicinity of chemicals. Never place chemicals in containers that are normally used for food or drink. Keep away from food, drink and animal feedingsuffs.

7.2 Conditions for safe storage, including any incompatibilities

Managing of associated risks

- Explosive atmospheres

Keep container tightly closed and in a well-ventilated place. Use local and general ventilation. Keep cool. Protect from sunlight.

- Flammability hazards

Keep away from sources of ignition - No smoking. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Take precautionary measures against static discharge. Protect from sunlight.

- Ventilation requirements

Use local and general ventilation. Ground/bond container and receiving equipment.

- Packaging compatibilities

Only packagings which are approved (e.g. acc. to the Dangerous Goods Regulations) may be used.

7.3 Specific end use(s)

See section 16 for a general overview.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limit values (Workplace Exposure Limits)

Country	Name of agent	CAS No	Identifier	TWA [ppm]	TWA [mg/m ³]	STEL [ppm]	STEL [mg/m ³]	Ceiling-C [ppm]	Ceiling-C [mg/m ³]	Notation	Source
US	2-butoxyethanol	111-76-2	REL	5 (10 h)	24 (10 h)						NIOSH REL
US	2-butoxyethanol	111-76-2	PEL	50	240						29 CFR 1910.1000
US	2-butoxyethanol (EGBE) (glycol monobutyl ether)	111-76-2	PEL (CA)	20	97						Cal/OSHA PEL
US	heptane (n-heptane)	142-82-5	PEL	500	2,000						29 CFR 1910.1000
US	n-heptane	142-82-5	PEL (CA)	400	1,600	500	2,000				Cal/OSHA PEL
US	n-heptane	142-82-5	REL	85 (10 h)	350 (10 h)			440 (15 min)	1,800 (15 min)		NIOSH REL
US	isopropyl alcohol	67-63-0	PEL (CA)	400	980	500	1,225				Cal/OSHA PEL

Tire & Trim

Version number: GHS 7.0
Replaces version of: 2018-06-21 (GHS 6)

Revision: 2019-06-14

Occupational exposure limit values (Workplace Exposure Limits)

Country	Name of agent	CAS No	Identifier	TWA [ppm]	TWA [mg/m ³]	STEL [ppm]	STEL [mg/m ³]	Ceiling-C [ppm]	Ceiling-C [mg/m ³]	Notation	Source
US	isopropyl alcohol	67-63-0	REL	400 (10 h)	980 (10 h)	500	1,225				NIOSH REL
US	isopropyl alcohol	67-63-0	PEL	400	980						29 CFR 1910.1000

Notation

Ceiling-C
STEL

ceiling value is a limit value above which exposure should not occur
short-term exposure limit: a limit value above which exposure should not occur and which is related to a 15-minute period (unless otherwise specified)

TWA

time-weighted average (long-term exposure limit): measured or calculated in relation to a reference period of 8 hours time-weighted average (unless otherwise specified)

Relevant DNELs of components of the mixture

Name of substance	CAS No	Endpoint	Threshold level	Protection goal, route of exposure	Used in	Exposure time
heptane	142-82-5	DNEL	300 mg/kg	human, dermal	worker (industry)	chronic - systemic effects
heptane	142-82-5	DNEL	2,085 mg/m ³	human, inhalatory	worker (industry)	chronic - systemic effects
2-butoxy-1-ethanol	111-76-2	DNEL	75 mg/kg	human, dermal	worker (industry)	chronic - systemic effects
2-butoxy-1-ethanol	111-76-2	DNEL	98 mg/m ³	human, inhalatory	worker (industry)	chronic - systemic effects
Propan-2-ol	67-63-0	DNEL	888 mg/kg	human, dermal	worker (industry)	chronic - systemic effects
Propan-2-ol	67-63-0	DNEL	500 mg/m ³	human, inhalatory	worker (industry)	chronic - systemic effects

Relevant PNECs of components of the mixture

Name of substance	CAS No	Endpoint	Threshold level	Organism	Environmental compartment	Exposure time
2-butoxy-1-ethanol	111-76-2	PNEC	8.8 mg/l	aquatic organisms	freshwater	short-term (single instance)
2-butoxy-1-ethanol	111-76-2	PNEC	0.88 mg/l	aquatic organisms	marine water	short-term (single instance)
2-butoxy-1-ethanol	111-76-2	PNEC	463 mg/l	microorganisms	sewage treatment plant (STP)	short-term (single instance)
2-butoxy-1-ethanol	111-76-2	PNEC	34.6 mg/kg	benthic organisms	sediment	short-term (single instance)
2-butoxy-1-ethanol	111-76-2	PNEC	3.13 mg/kg	terrestrial organisms	soil	short-term (single instance)
2-butoxy-1-ethanol	111-76-2	PNEC	9.1 mg/l	aquatic organisms	water	intermittent release

Tire & Trim

Version number: GHS 7.0
Replaces version of: 2018-06-21 (GHS 6)

Revision: 2019-06-14

Relevant PNECs of components of the mixture						
Name of substance	CAS No	End-point	Threshold level	Organism	Environmental compartment	Exposure time
Propan-2-ol	67-63-0	PNEC	140.9 mg/l	aquatic organisms	freshwater	short-term (single instance)
Propan-2-ol	67-63-0	PNEC	140.9 mg/l	aquatic organisms	marine water	short-term (single instance)
Propan-2-ol	67-63-0	PNEC	2,251 mg/l	microorganisms	sewage treatment plant (STP)	short-term (single instance)
Propan-2-ol	67-63-0	PNEC	552 mg/kg	benthic organisms	sediment	short-term (single instance)
Propan-2-ol	67-63-0	PNEC	552 mg/kg	pelagic organisms	sediment	short-term (single instance)
Propan-2-ol	67-63-0	PNEC	160 mg/kg	(top) predators	water	short-term (single instance)
Propan-2-ol	67-63-0	PNEC	28 mg/kg	terrestrial organisms	soil	short-term (single instance)
Propan-2-ol	67-63-0	PNEC	140.9 mg/l	aquatic organisms	water	intermittent re-release

8.2 Exposure controls

Appropriate engineering controls

General ventilation.

Individual protection measures (personal protective equipment)

Eye/face protection

Wear eye/face protection.

Skin protection

- Hand protection

Wear suitable gloves. Chemical protection gloves are suitable, which are tested according to EN 374. Check leak-tightness/impermeability prior to use. In the case of wanting to use the gloves again, clean them before taking off and air them well. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

- Other protection measures

Take recovery periods for skin regeneration. Preventive skin protection (barrier creams/ointments) is recommended. Wash hands thoroughly after handling.

Respiratory protection

In case of inadequate ventilation wear respiratory protection.

Environmental exposure controls

Use appropriate container to avoid environmental contamination. Keep away from drains, surface and ground water.

Tire & Trim

Version number: GHS 7.0
Replaces version of: 2018-06-21 (GHS 6)

Revision: 2019-06-14

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance

Physical state	liquid
Color	blue
Odor	fruity

Other safety parameters

pH (value)	not determined
Melting point/freezing point	not determined
Initial boiling point and boiling range	>65 °C at 1 atm
Flash point	<18.5 °C at 101.3 kPa
Evaporation rate	not determined
Flammability (solid, gas)	not relevant, (fluid)

Explosive limits

- Lower explosion limit (LEL)	0.6 vol%
- Upper explosion limit (UEL)	4.9 vol%
Vapor pressure	6.09 kPa at 25 °C
Density	not determined
Vapor density	this information is not available
Relative density	0.79 at 25 °C (water = 1)
Solubility(ies)	not determined

Partition coefficient

- n-octanol/water (log KOW)	this information is not available
Auto-ignition temperature	204 °C
Viscosity	not determined
Explosive properties	none
Oxidizing properties	none



Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

Tire & Trim

Version number: GHS 7.0
Replaces version of: 2018-06-21 (GHS 6)

Revision: 2019-06-14

9.2 Other information

Temperature class (USA, acc. to NEC 500)	T3 (maximum permissible surface temperature on the equipment: 200° C)
--	---

SECTION 10: Stability and reactivity

10.1 Reactivity

Concerning incompatibility: see below "Conditions to avoid" and "Incompatible materials". The mixture contains reactive substance(s). Risk of ignition.

If heated:

Risk of ignition

10.2 Chemical stability

See below "Conditions to avoid".

10.3 Possibility of hazardous reactions

No known hazardous reactions.

10.4 Conditions to avoid

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Hints to prevent fire or explosion

Use explosion-proof electrical/ventilating/lighting/equipment. Use only non-sparking tools. Take precautionary measures against static discharge.

10.5 Incompatible materials

Oxidizers

10.6 Hazardous decomposition products

Reasonably anticipated hazardous decomposition products produced as a result of use, storage, spill and heating are not known. Hazardous combustion products: see section 5.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Test data are not available for the complete mixture.

Classification procedure

The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

Classification acc. to OSHA "Hazard Communication Standard" (29 CFR 1910.1200)

Acute toxicity

Shall not be classified as acutely toxic.

GHS of the United Nations, annex 4: May be harmful if inhaled.

Acute toxicity estimate (ATE) of components of the mixture			
Name of substance	CAS No	Exposure route	ATE
2-butoxy-1-ethanol	111-76-2	oral	1,746 mg/kg
2-butoxy-1-ethanol	111-76-2	dermal	1,100 mg/kg
2-butoxy-1-ethanol	111-76-2	inhalation: vapor	11 mg/l/4h

Tire & Trim

Version number: GHS 7.0
Replaces version of: 2018-06-21 (GHS 6)

Revision: 2019-06-14

Skin corrosion/irritation

Causes skin irritation.

Serious eye damage/eye irritation

Shall not be classified as seriously damaging to the eye or eye irritant.

Respiratory or skin sensitization

Shall not be classified as a respiratory or skin sensitizer.

Germ cell mutagenicity

Shall not be classified as germ cell mutagenic.

Carcinogenicity

Shall not be classified as carcinogenic.

IARC Monographs on the Evaluation of Carcinogenic Risks to Humans			
Name of substance	CAS No	Classification	Number
2-butoxy-1-ethanol	111-76-2	3	
Propan-2-ol	67-63-0	3	

Legend

3 Not classifiable as to carcinogenicity in humans

Reproductive toxicity

Shall not be classified as a reproductive toxicant.

Specific target organ toxicity - single exposure

May cause drowsiness or dizziness.

Specific target organ toxicity - repeated exposure

Shall not be classified as a specific target organ toxicant (repeated exposure).

Aspiration hazard

May be fatal if swallowed and enters airways.

SECTION 12: Ecological information

12.1 Toxicity

Toxic to aquatic life with long lasting effects.

Aquatic toxicity (acute) of components of the mixture					
Name of substance	CAS No	Endpoint	Value	Species	Exposure time
heptane	142-82-5	EC50	1.5 mg/l	aquatic invertebrates	48 h
2-butoxy-1-ethanol	111-76-2	LC50	1,474 mg/l	fish	96 h
2-butoxy-1-ethanol	111-76-2	EC50	1,550 mg/l	aquatic invertebrates	48 h
2-butoxy-1-ethanol	111-76-2	ErC50	1,840 mg/l	algae	72 h
Propan-2-ol	67-63-0	LC50	10,000 mg/l	fish	96 h

Tire & Trim

Version number: GHS 7.0
Replaces version of: 2018-06-21 (GHS 6)

Revision: 2019-06-14

Aquatic toxicity (chronic) of components of the mixture					
Name of substance	CAS No	Endpoint	Value	Species	Exposure time
2-butoxy-1-ethanol	111-76-2	EC50	297 mg/l	aquatic invertebrates	21 d
Propan-2-ol	67-63-0	LC50	>10,000 mg/l	aquatic invertebrates	24 h

12.2 Persistence and degradability

Data are not available.

12.3 Bioaccumulative potential

Data are not available.

12.4 Mobility in soil

Data are not available.

12.5 Results of PBT and vPvB assessment

Data are not available.

12.6 Other adverse effects

Endocrine disrupting potential

None of the ingredients are listed.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Waste treatment-relevant information

Solvent reclamation/regeneration.

Sewage disposal-relevant information

Do not empty into drains. Avoid release to the environment. Refer to special instructions/safety data sheets.

Waste treatment of containers/packages

Only packagings which are approved (e.g. acc. to DOT) may be used. Completely emptied packages can be recycled. Handle contaminated packages in the same way as the substance itself.

Remarks

Please consider the relevant national or regional provisions. Waste shall be separated into the categories that can be handled separately by the local or national waste management facilities.

SECTION 14: Transport information

14.1 UN number	1993
14.2 UN proper shipping name	Flammable liquid, n.o.s.
14.3 Transport hazard class(es)	
Class	3 (flammable liquids)
14.4 Packing group	II (substance presenting medium danger)
14.5 Environmental hazards	hazardous to the aquatic environment
Environmentally hazardous substance (aquatic environment)	heptane

Tire & Trim

Version number: GHS 7.0
Replaces version of: 2018-06-21 (GHS 6)

Revision: 2019-06-14

14.6 Special precautions for user

There is no additional information.

14.7 Transport in bulk according to Annex II of MARPOL and the IBC Code

The cargo is not intended to be carried in bulk.

Information for each of the UN Model Regulations

Transport of dangerous goods by road or rail (49 CFR US DOT)

Index number	1993
Proper shipping name	Flammable liquid, n.o.s.
- Particulars in the shipper's declaration	UN1993, Flammable liquid, n.o.s., 3, II, environmentally hazardous
Class	3
Packing group	II
Danger label(s)	3, fish and tree



Environmental hazards	yes (hazardous to the aquatic environment)
Special provisions (SP)	IB2, T7, TP1, TP8, TP28
ERG No	128

International Maritime Dangerous Goods Code (IMDG)

UN number	1993
Proper shipping name	FLAMMABLE LIQUID, N.O.S.
Class	3
Marine pollutant	yes (hazardous to the aquatic environment)
Packing group	II
Danger label(s)	3, fish and tree



Special provisions (SP)	274
Excepted quantities (EQ)	E2
Limited quantities (LQ)	1 L
EmS	F-E, <u>S-E</u>
Stowage category	B

International Civil Aviation Organization (ICAO-IATA/DGR)

UN number	1993
Proper shipping name	Flammable liquid, n.o.s.
Class	3
Environmental hazards	yes (hazardous to the aquatic environment)
Packing group	II



Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

Tire & Trim

Version number: GHS 7.0
Replaces version of: 2018-06-21 (GHS 6)

Revision: 2019-06-14

Danger label(s)	3
	
Special provisions (SP)	A3
Excepted quantities (EQ)	E2
Limited quantities (LQ)	1 L

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations specific for the product in question

National regulations (United States)

15.1.5 Toxic Substance Control Act (TSCA) all ingredients are listed
0.1

Superfund Amendment and Reauthorization Act (SARA TITLE III)

- The List of Extremely Hazardous Substances and Their Threshold Planning Quantities (EPCRA Section 302, 304)

none of the ingredients are listed

- Specific Toxic Chemical Listings (EPCRA Section 313)

Toxics Release Inventory: Specific Toxic Chemical Listings			
Name acc. to inventory	CAS No	Remarks	Effective date
isopropyl alcohol	67-63-0	only persons who manufacture by the strong acid process are subject, supplier notification not required	1986-12-31

Comprehensive Environmental Response, Compensation, and Liability Act (CERCLA)

- List of Hazardous Substances and Reportable Quantities (CERCLA section 102a) (40 CFR 302.4)

none of the ingredients are listed

Clean Air Act

none of the ingredients are listed

15.1.5 New Jersey Worker and Community Right to Know Act
0.5

Right to Know Hazardous Substance List			
Name acc. to inventory	CAS No	Remarks	Classifications
n-heptane	142-82-5		F3
2-BUTOXY ETHANOL (ETHANOL, 2-BUTOXY-, BUTYL CELLOSOLVE)	111-76-2		CA F2
isopropyl alcohol	67-63-0		F3

Legend

CA Carcinogenic
F2 Flammable - Second Degree
F3 Flammable - Third Degree



Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

Tire & Trim

Version number: GHS 7.0
Replaces version of: 2018-06-21 (GHS 6)

Revision: 2019-06-14

15.1.5 California Environmental Protection Agency (Cal/EPA): Proposition 65 - Safe Drinking Water and Toxic Enforcement Act of 1987

0.6 none of the ingredients are listed

Industry or sector specific available guidance(s)

NPCA-HMIS® III

Hazardous Materials Identification System. American Coatings Association.

Category	Rating	Description
Chronic	/	none
Health	2	temporary or minor injury may occur
Flammability	3	material that can be ignited under almost all ambient temperature conditions
Physical hazard	0	material that is normally stable, even under fire conditions, and will not react with water, polymerize, decompose, condense, or self-react. Non-explosive
Personal protection	-	

Chronic: chronic hazard
Flammability: flammability hazard
Health: health hazard
Personal protection: personal protective equipment (PPE) for normal use
Physical hazard: reactivity

NFPA® 704

National Fire Protection Association: Standard System for the Identification of the Hazards of Materials for Emergency Response (United States).

Category	Degree of hazard	Description
Flammability	3	material that can be ignited under almost all ambient temperature conditions
Health	2	material that, under emergency conditions, can cause temporary incapacitation or residual injury
Instability	0	material that is normally stable, even under fire conditions
Special hazard		

National inventories

Country	Inventory	Status
CA	DSL	all ingredients are listed
EU	REACH Reg.	not all ingredients are listed
US	TSCA	all ingredients are listed

Legend

DSL Domestic Substances List (DSL)
REACH Reg. REACH registered substances
TSCA Toxic Substance Control Act

15.2 Chemical Safety Assessment

Chemical safety assessments for substances in this mixture were not carried out.



Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

Tire & Trim

Version number: GHS 7.0
Replaces version of: 2018-06-21 (GHS 6)

Revision: 2019-06-14

SECTION 16: Other information, including date of preparation or last revision

Indication of changes (revised safety data sheet)

Section	Former entry (text/value)	Actual entry (text/value)	Safety-relevant
1.3	e-mail (competent person): bblahnik@bbblending.com (Robert Blahnik)	e-mail (competent person): btirrell@bbblending.com	yes
1.4	Emergency information service: USA 1.800.535.5053, INTL 1.352.323.3500 This number is only available during the following of- fice hours: Mon-Fri 09:00 AM - 05:00 PM	Emergency information service: USA 1.800.535.5053, INTL 1.352.323.3500 24 hr emergency information	yes
3.2		Hazardous ingredients acc. to GHS: change in the listing (table)	yes
4.1	Following eye contact: Remove contact lenses, if present and easy to do. Continue rinsing. Irrigate copiously with clean, fresh water for at least 10 minutes, holding the eyelids apart.	Following eye contact: Remove contact lenses, if present and easy to do. Continue rinsing.	yes
4.2	Most important symptoms and effects, both acute and delayed: Narcotic effects.		yes
4.3	Indication of any immediate medical attention and special treatment needed: none		yes
6.2	Environmental precautions: Keep away from drains, surface and ground water. Retain contaminated washing water and dispose of it.	Environmental precautions: Keep away from drains, surface and ground water. Retain contaminated washing water and dispose of it. If substance has entered a water course or sew- er, inform the responsible authority.	yes
8.1		Occupational exposure limit values (Workplace Ex- posure Limits): change in the listing (table)	yes
9.1	Density: 0.7655 g/ml	Density: not determined	yes
11.1		IARC Monographs on the Evaluation of Carcinogen- ic Risks to Humans: change in the listing (table)	yes
12.1		Aquatic toxicity (acute) of components of the mix- ture: change in the listing (table)	yes
12.1		Aquatic toxicity (chronic) of components of the mix- ture: change in the listing (table)	yes
14.2	Technical name (hazardous ingredients): heptane		yes
14.5	Environmental hazards: non-environmentally hazardous acc. to the danger- ous goods regulations	Environmental hazards: hazardous to the aquatic environment	yes
14.5		Environmentally hazardous substance (aquatic en- vironment): heptane	yes
14.7	Particulars in the shipper's declaration: UN1993, Flammable liquid, n.o.s., (contains: heptane), 3, II	Particulars in the shipper's declaration: UN1993, Flammable liquid, n.o.s., 3, II, environ- mentally hazardous	yes



Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

Tire & Trim

Version number: GHS 7.0
Replaces version of: 2018-06-21 (GHS 6)

Revision: 2019-06-14

Section	Former entry (text/value)	Actual entry (text/value)	Safety-relevant
14.7	Danger label(s): 3	Danger label(s): 3, fish and tree	yes
14.7		Danger label(s): change in the listing (table)	yes
14.7		Environmental hazards: yes (hazardous to the aquatic environment)	yes
14.7	Marine pollutant: -	Marine pollutant: yes (hazardous to the aquatic environment)	yes
14.7	Danger label(s): 3	Danger label(s): 3, fish and tree	yes
14.7		Danger label(s): change in the listing (table)	yes
14.7		Environmental hazards: yes (hazardous to the aquatic environment)	yes
15.1.50.1		Toxic Substance Control Act (TSCA): all ingredients are listed	yes
15.1.50.1		Toxics Release Inventory: Specific Toxic Chemical Listings: change in the listing (table)	yes
15.1.50.6		National inventories	yes
15.1.50.6		National inventories: change in the listing (table)	yes

Abbreviations and acronyms

Abbr.	Descriptions of used abbreviations
29 CFR 1910.1000	29 CFR 1910.1000, Tables Z-1, Z-2, Z-3 - Occupational Safety and Health Standards: Toxic and Hazardous Substances (permissible exposure limits)
49 CFR US DOT	49 CFR § 40 U.S. Department of Transportation
Acute Tox.	Acute toxicity
Asp. Tox.	Aspiration hazard
ATE	Acute Toxicity Estimate
Cal/OSHA PEL	California Division of Occupational Safety and Health (Cal/OSHA): Permissible Exposure Limits (PELs)
CAS	Chemical Abstracts Service (service that maintains the most comprehensive list of chemical substances)
Ceiling-C	Ceiling value
DGR	Dangerous Goods Regulations (see IATA/DGR)
DNEL	Derived No-Effect Level
DOT	Department of Transportation (USA)
EmS	Emergency Schedule
ERG No	Emergency Response Guidebook - Number
Eye Dam.	Seriously damaging to the eye
Eye Irrit.	Irritant to the eye
Flam. Liq.	Flammable liquid



Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

Tire & Trim

Version number: GHS 7.0
Replaces version of: 2018-06-21 (GHS 6)

Revision: 2019-06-14

Abbr.	Descriptions of used abbreviations
GHS	"Globally Harmonized System of Classification and Labelling of Chemicals" developed by the United Nations
IATA	International Air Transport Association
IATA/DGR	Dangerous Goods Regulations (DGR) for the air transport (IATA)
ICAO	International Civil Aviation Organization
IMDG	International Maritime Dangerous Goods Code
MARPOL	International Convention for the Prevention of Pollution from Ships (abbr. of "Marine Pollutant")
NIOSH REL	National Institute for Occupational Safety and Health (NIOSH): Recommended Exposure Limits (RELs)
NPCA-HMIS® III	National Paint and Coatings Association: Hazardous Materials Identification System - HMIS® III, Third Edition
OSHA	Occupational Safety and Health Administration (United States)
PBT	Persistent, Bioaccumulative and Toxic
PEL	Permissible exposure limit
PNEC	Predicted No-Effect Concentration
ppm	Parts per million
Skin Corr.	Corrosive to skin
Skin Irrit.	Irritant to skin
STEL	Short-term exposure limit
STOT SE	Specific target organ toxicity - single exposure
TWA	Time-weighted average
vPvB	Very Persistent and very Bioaccumulative

Key literature references and sources for data

OSHA Hazard Communication Standard (HCS), 29 CFR 1910.1200.

Transport of dangerous goods by road or rail (49 CFR US DOT). International Maritime Dangerous Goods Code (IMDG). Dangerous Goods Regulations (DGR) for the air transport (IATA).

Classification procedure

Physical and chemical properties: The classification is based on tested mixture.

Health hazards, Environmental hazards: The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

List of relevant phrases (code and full text as stated in chapter 2 and 3)

Code	Text
H225	Highly flammable liquid and vapor.
H227	Combustible liquid.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H312	Harmful in contact with skin.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.



Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

Tire Trim

Version number: GHS 7.0
Replaces version of: 2018-06-21 (GHS 6)

Revision: 2019-06-14

Code	Text
H336	May cause drowsiness or dizziness.

Disclaimer

This information is based upon the present state of our knowledge. This SDS has been compiled and is solely intended for this product.